SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
UK REACH Regulations (SI 2019/758 as amended)

Revision date 04/07/2025 **Revision Number** 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code(s) 1769

Product Name 1769 - Toyota Material Handling UK Limited - Prolift Cockpit Spray 400ml Aerosols

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Lubricant

1.3. Details of the supplier of the safety data sheet

Manufacturer

Specialised Chemicals Ltd
Tollemache Road South
Spittlegate Level Industrial Estate
Grantham
Lincolnshire
NG317UH
Tel: +44 (0) 1476 567615

For further information, please contact;

Emergency Telephone +44(0)1476 567615 (Mon to Fri 09:00 - 17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Skin corrosion/irritation	Category 2 - (H315)
Hazardous to the aquatic environment - chronic	Category 3 - (H412)
Aerosols	Category 1 - (H222, H229)

2.2. Label elements



Signal word
Danger

Hazard statements
H315 - Causes skin irritation
H412 - Harmful to aquatic life with long lasting effects
H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated

Precautionary statements
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P261 - Avoid breathing vapours/spray
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	EC No (EU Index No)	UK REACH registration number	Classification according to GB CLP (SI 2020/1567 as amended)	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE 68476-85-7	60-100%	() 270-704-2	-	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	10-30%	() 265-151-9	-	Flam. Liq. 2 (H225 Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aquatic Chronic 2 (H411)	-	-	-

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >= 0.1% (UK REACH Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate

ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals.

7.3. Specific end use(s)

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	United Kingdom
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE 68476-85-7	TWA: 1000 ppm TWA: 1750 mg/m³ STEL: 1250 ppm STEL: 2180 mg/m³

Biological occupational exposure limits This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Derived No Effect Level (DNEL) - Workers No information available

Chemical name	Oral	Dermal	Inhalation
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE 68476-85-7		23.4 mg/kg bw/day [4] [6]	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0			1286.4 mg/m³ [4] [7] 837.5 mg/m³ [5] [6] 1066.67 mg/m³ [5] [7]

Derived No Effect Level (DNEL) - General Public No information available.

Chemical name	Oral	Dermal	Inhalation
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0			1152 mg/m³ [4] [7] 178.57 mg/m³ [5] [6] 640 mg/m³ [5] [7]

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering controls No information available.

Personal protective equipment

Eye/face protection Tight sealing safety goggles. Safety glasses with side shields are recommended for medical or industrial exposures.

Hand protection Impervious gloves. Wear suitable gloves.

Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Aerosol
Colour	clear
Odour	Sweet.

Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	-41 - 250 °C	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	9.5	
Lower flammability or explosive limits	1.2	
Flash point	<-40	CC (closed cup)
Autoignition temperature	246 °C	None known
Decomposition temperature		None known
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	21	None known
Dynamic viscosity	No data available	None known
Water solubility	Insoluble in water	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	0.608	None known
Bulk density	No data available	
Liquid Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size		
Particle Size Distribution		
Explosive properties	No information available	
Oxidising properties	No information available	

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data
Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	27,295.10	mg/kg
ATEmix (dermal)	13,536.30	mg/kg
ATEmix (inhalation-gas)	99,999.00	ppm
ATEmix (inhalation-dust/mist)	99,999.00	mg/l

ATEmix (inhalation-vapour) 99,999.00 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitisation No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	-	LC50: =8.41mg/L (96h, Oncorhynchus mykiss)	-	EC50: <0.26mg/L (48h, Daphnia magna)

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE	<=2.8

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical name	PBT and vPvB assessment
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE	The substance is not PBT / vPvB
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

SECTION 14: Transport information

IATA

14.1 UN number or ID number UN1950
14.2 UN proper shipping name Aerosols, flammable
14.3 Transport hazard class(es) 2.1
14.4 Packing group Not regulated
Description UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards Yes
14.6 Special precautions for user
Special Provisions A145, A167, A802
ERG Code 10L

IMDG

14.1 UN number or ID number UN1950
14.2 UN proper shipping name Aerosols
14.3 Transport hazard class(es) 2.1
14.4 Packing group Not regulated
Description UN1950, Aerosols, 2.1
14.5 Environmental hazards Yes
14.6 Special precautions for user
Special Provisions 63,190, 277, 327, 344, 381, 959
EmS-No. F-D, S-U
14.7 Maritime transport in bulk according to IMO instruments

RID

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	190, 327, 344, 625
Classification code	5F

ADR

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1, (D)
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	190, 327, 344, 625
Classification code	5F
Tunnel restriction code	(D)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Authorisations and/or restrictions on use:
This product does not contain substances subject to authorisation (UK REACH - Annex XIV). This product does not contain substances subject to restriction (UK REACH - Annex XVII).

Persistent Organic Pollutants
Not applicable

Export Notification requirements
Not applicable

Dangerous substance category per COMAH (SI 2015/483 as amended)
P3a - FLAMMABLE AEROSOLS
P3b - FLAMMABLE AEROSOLS

Named dangerous substances per COMAH (SI 2015/483 as amended)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE - 68476-85-7	50	200
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics - 64742-49-0	-	25000

The Ozone-Depleting Substances Regulations 2015
Not applicable

The Biocidal Products Regulations 2001 (as amended)
Not applicable

The Water Environment (Water Framework Directive) (England and Wales) Regulations 2017 (as amended)
Not applicable

Poisons and Explosive Precursors
Not applicable

International Inventories

TSCA	See inventories below
DSL/NDSL	See inventories below
EINECS/ELINCS	See inventories below
ENCS	See inventories below
IECSC	See inventories below
KECL	See inventories below
PICCS	See inventories below
AIIC	See inventories below
NZIoC	See inventories below

Legend:
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AIIC - Australian Inventory of Industrial Chemicals
NZIoC - New Zealand Inventory of Chemicals

15.2. Chemical safety assessment

Chemical Safety Report No information available

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15
H220 - Extremely flammable gas
H280 - Contains gas under pressure; may explode if heated

Legend
SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation
+	Sensitisers		

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method

Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Chronic aquatic toxicity	Calculation method
Acute aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method
Flammable aerosol	On basis of test data

Key literature references and sources for data used to compile the SDS
Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australian National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine’s PubMed database (NLM PUBMED)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision date 04/07/2025

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)
Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

UK SDS version information - XGHS
UL release:
GHS Revision 7
2022 Q1

United Kingdom Full process, including GHS and Transportation Wizards

Full text of any hazard and/or precautionary statements referred to under Sections 2-15
H220 - Extremely flammable gas H280 - Contains gas under pressure; may explode if heated

Chemical name	Classification according to GB CLP (SI 2020/1567 as amended)	Specific concentration limit (SCL)
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE	Flam. Gas 1 (H220) Press. Gas (H280)	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Flam. Liq. 2 (H225 Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aquatic Chronic 2 (H411)	