SAFETY DATA SHEET
MASTER SVART MELLANMATT 28168

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

Part No: 28168 - Spray Paint

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MASTER SVART MELLANMATT 28168

Product number 11334

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Touch-up paint for forklifts

1.3. Details of the supplier of the safety data sheet

Supplier

Spray Master AB
Fabriksvägen 5
Box 1050
S-186 26 Vallentuna
Sweden
Tel: +46 (8) 505 133 00
Fax: +46 (8) 505 133 01
Info@spraymaster.se

1.4. Emergency telephone number

National emergency telephone number Giftinformation 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)


Physical hazards Aerosol 1 - H222, H229

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

MASTER SVART MELLANMATT 28168

Precautionary statements	P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	ETHYL ACETATE, BUTYL ACETATE -norm, 1-METHOXY-2-PROPANOL
Supplementary precautionary statements	P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/ doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/ attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ETHYL ACETATE **25-35%**

CAS number: 141-78-6 | EC number: 205-500-4 | REACH registration number: 01-2119475103-46

Classification
Flam. Liq. 2 - H225
Eye Irrit. 2 - H319
STOT SE 3 - H336

BUTYL ACETATE -norm **25-35%**

CAS number: 123-86-4 | EC number: 204-658-1 | REACH registration number: 01-2119485493-29-0000

Classification
Flam. Liq. 3 - H226
STOT SE 3 - H336

DIMETHYL ETHER **15-24.9%**

CAS number: 115-10-6 | EC number: 204-065-8 | REACH registration number: 01-2119472128-37

Classification
Flam. Gas 1 - H220
Press. Gas, Compressed - H280

MASTER SVART MELLANMATT 28168

BUTANE		**5-7.49%**
CAS number: 106-97-8	EC number: 203-448-7	REACH registration number: 01-2119474691-32
Classification Flam. Gas 1 - H220 Press. Gas, Compressed - H280		
PROPANE		**5-7.49%**
CAS number: 74-98-6	EC number: 200-827-9	REACH registration number: 01-2119486944-21
Classification Flam. Gas 1 - H220 Press. Gas, Compressed - H280		
1-METHOXY-2-PROPANOL		**2.5-4.99%**
CAS number: 107-98-2	EC number: 203-539-1	REACH registration number: 01-2119457435-35-0000
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336		
ETHANOL		**1-1.99%**
CAS number: 64-17-5	EC number: 200-578-6	REACH registration number: 01-2119457610-43
Classification Flam. Liq. 2 - H225		
PENTANE		**<0.099%**
CAS number: 109-66-0	EC number: 203-692-4	REACH registration number: 01-2119459286-30-0000
Classification Flam. Liq. 2 - H225 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

MASTER SVART MELLANMATT 28168

Ingestion	Drink a few glasses of water or milk. Do not induce vomiting.
Skin contact	Wash skin thoroughly with soap and water.
Eye contact	Rinse with water. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	Solvent abuse can kill instantly.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea. May cause drowsiness or dizziness.
Ingestion	May cause nausea, headache, dizziness and intoxication.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Extremely flammable.

5.3. Advice for firefighters

Protective actions during firefighting	Containers close to fire should be removed or cooled with water.
Special protective equipment for firefighters	Wear chemical protective suit. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Large Spillages: Contain and absorb spillage with sand, earth or other non-combustible material. Small Spillages: Wipe away with paper or textile fabric.

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Keep away from heat, sparks and open flame. Protect against direct sunlight. Avoid eating, drinking and smoking when using the product.

7.2. Conditions for safe storage, including any incompatibilities

MASTER SVART MELLANMATT 28168

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep container dry.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm
Short-term exposure limit (15-minute): WEL 400 ppm

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³
Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

DIMETHYL ETHER

Long-term exposure limit (8-hour TWA): WEL 400 ppm 766 mg/m³
Short-term exposure limit (15-minute): WEL 500 ppm 958 mg/m³

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³
Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

PROPANE

Short-term exposure limit (15-minute): WEL No reference standard

1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m³
Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m³
Sk

ETHANOL

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³
Short-term exposure limit (15-minute): WEL

PENTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1800 mg/m³
Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit
Sk = Can be absorbed through the skin.

BUTYL ACETATE -norm (CAS: 123-86-4)

DNEL

Industry - Inhalation; Short term systemic effects: 960 mg/m³
Industry - Inhalation; Short term local effects: 960 mg/m³
Industry - Inhalation; Long term systemic effects: 480 mg/m³
Industry - Inhalation; Long term local effects: 480 mg/m³
Consumer - Inhalation; Short term systemic effects: 859.7 mg/m³
Consumer - Inhalation; Short term local effects: 859.7 mg/m³
Consumer - Inhalation; Long term systemic effects: 102.34 mg/m³
Consumer - Inhalation; Long term local effects: 102.34 mg/m³

MASTER SVART MELLANMATT 28168

PNEC

- Fresh water; 0.18 mg/l
- Marine water; 0.018 mg/l
- Intermittent release; 0.36 mg/l
- STP; 35.6 mg/l
- Sediment (Freshwater); 0.981 mg/kg
- Sediment (Marinewater); 0.0981 mg/kg
- Soil; 0.0903 mg/kg

DIMETHYL ETHER (CAS: 115-10-6)

DNEL

Professional - Inhalation; Long term systemic effects: 1894 mg/m³
Consumer - Inhalation; Long term systemic effects: 471 mg/m³

PNEC

- Fresh water; 0,155 mg/l
- Marine water; 0,016 mg/l
- Sediment (Freshwater); 0,681 mg/kg
- Sediment (Marinewater); 0,069 mg/kg
- Soil; 0,045 mg/kg

PENTANE (CAS: 109-66-0)

PNEC

- water; 0,027 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

All handling should only take place in well-ventilated areas.

Eye/face protection

Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Chemical splash goggles.

Hand protection

For prolonged or repeated skin contact use suitable protective gloves. Wear protective gloves made of the following material: Nitrile rubber.

Other skin and body protection

Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection

In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P3).

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Aerosol.

Colour

Black.

Odour

Organic solvents.

Odour threshold

Not determined.

pH

Not determined.

Melting point

Not determined.

MASTER SVART MELLANMATT 28168

Initial boiling point and range	Not determined.
Flash point	Technical impossibility to obtain the data.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Other flammability	Not determined.
Vapour pressure	410-420 kPa @ 20°C
Vapour density	Not determined.
Relative density	~0,8
Bulk density	Not determined.
Solubility(ies)	No specific test data are available. Organic solvents.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not determined.
Explosive properties	Not determined.
Explosive under the influence of a flame	Yes
Oxidising properties	Not determined.

9.2. Other information

Other information	Not relevant.
Refractive index	Not determined.
Particle size	Not determined.
Molecular weight	Not determined.
Volatility	Highly volatile.
Saturation concentration	Not determined.
Critical temperature	Not determined.
Volatile organic compound	Category: special finishes. VOC limit: 840 g/l This product contains a maximum VOC content of 657 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

MASTER SVART MELLANMATT 28168

Possibility of hazardous reactions Not known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Not known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No data is available regarding the preparation it self.

Acute toxicity - oral

Notes (oral LD_{50}) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD_{50}) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC_{50}) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Does not contain any substances known to be mutagenic.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Reproductive toxicity

Reproductive toxicity - fertility Does not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Not relevant.

MASTER SVART MELLANMATT 28168

General information	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	May cause drowsiness or dizziness. Vapours have a narcotic effect. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. May cause respiratory system irritation.
Ingestion	May cause irritation. Symptoms following overexposure may include the following: Stomach pain. Nausea, vomiting. Diarrhoea.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	Irritation of eyes and mucous membranes.
Acute and chronic health hazards	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Nausea, vomiting. Headache.

Toxicological information on ingredients.

ETHYL ACETATE

Acute toxicity - oral

Acute toxicity oral (LD_{50} mg/kg)	5,620.0
Species	Rat

Acute toxicity - dermal

Acute toxicity dermal (LD_{50} mg/kg)	18,000.0
Species	Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation (LC_{50} vapours mg/l)	5.77
Species	Rat
ATE inhalation (vapours mg/l)	5.77

BUTYL ACETATE -norm

Acute toxicity - oral

Acute toxicity oral (LD_{50} mg/kg)	10,768.0
Species	Rat

Acute toxicity - dermal

Acute toxicity dermal (LD_{50} mg/kg)	17,600.0
Species	Rabbit

Acute toxicity - inhalation

MASTER SVART MELLANMATT 28168

Acute toxicity inhalation (LC_{50} vapours mg/l)	40.0
Species	Rat
ATE inhalation (vapours mg/l)	40.0

DIMETHYL ETHER

Acute toxicity - oral

Notes (oral LD_{50})	Not applicable.

Acute toxicity - dermal

Notes (dermal LD_{50})	Not applicable.
Skin contact	Risk of frostbite.

BUTANE

Acute toxicity - oral

Notes (oral LD_{50})	Not applicable.

Acute toxicity - dermal

Notes (dermal LD_{50})	Not applicable.

Acute toxicity - inhalation

Acute toxicity inhalation (LC_{50} vapours mg/l)	20.0
Notes (inhalation LC_{50})	

PROPANE

Acute toxicity - oral

Notes (oral LD_{50})	Not applicable.

Acute toxicity - dermal

Notes (dermal LD_{50})	Not applicable.

Acute toxicity - inhalation

Acute toxicity inhalation (LC_{50} vapours mg/l)	20.0
Notes (inhalation LC_{50})	

ETHANOL

Acute toxicity - oral

Acute toxicity oral (LD_{50} mg/kg)	7,060.0
Species	Rat

Acute toxicity - dermal

MASTER SVART MELLANMATT 28168

Acute toxicity dermal (LD_{50} mg/kg)	20,000.0
Species	Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation (LC_{50} vapours mg/l)	124.7
Species	Rat
ATE inhalation (vapours mg/l)	124.7

PENTANE

Acute toxicity - oral

Acute toxicity oral (LD_{50} mg/kg)	400.0
Species	Rat

Acute toxicity - dermal

Acute toxicity dermal (LD_{50} mg/kg)	3,000.0
Species	Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation (LC_{50} vapours mg/l)	364.0
Species	Rat
ATE inhalation (vapours mg/l)	364.0

SECTION 12: Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

12.1. Toxicity

Toxicity No data is available regarding the preparation itself.

Ecological information on ingredients.

ETHYL ACETATE

Acute toxicity - fish	LC50, 96 hours: 230 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EC_{50}, 48 hours: 154 - 717 mg/l, Daphnia magna EC_{50}, 48 hours: mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC_{50}, 48 hours: 3300 mg/l, Scenedesmus subspicatus

BUTYL ACETATE -norm

Acute toxicity - fish	LC50, 96 hours: 18 mg/l, Pimephales promelas (Fat-head Minnow)

MASTER SVART MELLANMATT 28168

Acute toxicity - aquatic invertebrates	EC_{50}, 48 hours: 10-100 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC_{50}, 72 hours: 674,7 mg/l, Scenedesmus subspicatus

DIMETHYL ETHER

Acute toxicity - fish	LC50, 96 hours: > 4.1 mg/l, Poecilia reticulata (Guppy)
Acute toxicity - aquatic invertebrates	EC_{50}, 48 hours: > 4.4 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC_{50}, 96 hours: 154.9 mg/l, Freshwater algae

BUTANE

Acute toxicity - fish	Highly volatile. LC50, 96 hours: 24.11 mg/l,
Acute toxicity - aquatic invertebrates	Highly volatile. EC_{50}, 48 hours: 14.22 mg/l, Daphnia magna

PROPANE

Acute toxicity - aquatic invertebrates	Highly volatile. EC_{50}, 48 hours: 27.14 mg/l,
Acute toxicity - aquatic plants	, : ,

ETHANOL

Acute toxicity - fish	LC50, 96 hours: ~ 13500 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EC_{50}, 48 hours: ~ 5400 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC_{50}, 72 hours: > 10.9 mg/l, Marinewater algae

PENTANE

Acute toxicity - fish	LC50, 96 hours: 4,26 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC_{50}, 48 hours: 2,7-9,1 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC_{50}, 72 hours: 7,51 mg/l, Selenastrum capricornutum

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients.

ETHYL ACETATE

MASTER SVART MELLANMATT 28168

Persistence and degradability Readily biodegradable.

BUTYL ACETATE -norm

Biodegradation - Degradation (%) 98: 28 days
OECD 301C

DIMETHYL ETHER

Persistence and degradability The product is not readily biodegradable.

BUTANE

Persistence and degradability The product is readily biodegradable.

PROPANE

Persistence and degradability The product is readily biodegradable.

Biodegradation Water - :

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

BUTYL ACETATE -norm

Bioaccumulative potential BCF: 14,

Partition coefficient log Pow: 1,81

DIMETHYL ETHER

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

BUTANE

Bioaccumulative potential The product is not bioaccumulating.

PROPANE

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient :

ETHANOL

Bioaccumulative potential BCF: ~ 0.66,

Partition coefficient log Pow: ~ -0.32

MASTER SVART MELLANMATT 28168

PENTANE

Bioaccumulative potential BCF: 171,

Partition coefficient log Pow: 3,4

12.4. Mobility in soil

Mobility No information available

Ecological information on ingredients.

DIMETHYL ETHER

Adsorption/desorption coefficient Water - Koc: ~ 7.759 @ °C

BUTANE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

PROPANE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The manufacturer of this product complies with the rules and regulations of the European Parliament and Council Directive 94/62/EC of 20 December 1994 on packaging and packaging waste, by paying packaging fees for disposal and recycling of packaging waste.

Disposal methods The plastic lid and valve are sorted as plastic. Empty aerosols are sorted as scrap metal. Residues and non empty containers should be taken care of as hazardous waste according to local and national regulations.

Waste class Non empty containers: EWC code 08 01 11*
Empty containers: EWC code 15 01 04

SECTION 14: Transport information

General Aerosols may be carried domestically as limited quantities (1L) as long as each package does not exceed 30 kg in cardboard boxes or 20 kg on trays with shrink- or stretch wrapping. Each package shall be marked with diamond-shaped area, the top and bottom part is black, surrounded by a line that measures at least 100 mm x 100 mm.

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

MASTER SVART MELLANMATT 28168

UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	COUNCIL DIRECTIVE of may 1975 on the approximation of the laws of the Member States relating to aerosol dispensers.

MASTER SVART MELLANMATT 28168

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information A review of safety data sheet with staff to manage the product recommended.

Revision comments This is first issue.

Issued by Björkstedt

Revision date 13/11/2017

Revision 2

Supersedes date 10/09/2015

Hazard statements in full
H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: may burst if heated
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.