TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 04110R-JAM

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	DE-GREASER 04110R	Pseudonym	De-Greaser Spray
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance. Use; less than daily, seconds at a time.	Location of process being carried out	Customer Site, Toyota workshops

Identify the persons at risk	Team members ☑	Sub-contractors ☐	Customer Team member ☐	Public ☐

Labelling Elements


☐ Explosive


☑ Health Hazard


☐ Serious Health Hazard


☐ Oxidising


☐ Corrosive


☐ Acute


☑ Flammable


☐ Environmental


☐ Gas

Signal Word: Danger

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	☑	☑	☐	☐	☐	☐	☐

Additional Information: Aerosol

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
☑	☑	☑	☐	☐

Additional Information: Irritant. May cause drowsiness or dizziness.

Control Measures

Not expected to present a significant hazard under anticipated conditions of normal use.
Extremely flammable aerosol. Keep away from heat/sparks/open flames/hot surfaces. Pressurized container: Do not pierce or burn, even after use. - No smoking.
Use in a well-ventilated area. Avoid breathing vapour/spray.

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

Wear appropriate PPE as per SWP-32.

This product may have an adverse environmental impact; follow manufactures instructions during use and disposal.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes ☐	No ☑

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: 04110R-JAM

Provide details:

Personal Protective Equipment Required							
 ☐	 ☐	 ☐	 ☑	 ☑	 ☑	 ☑	 ☐
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other

Additional Information: Respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

First Aid Measures	
Inhalation:	Remove person to fresh air and keep comfortable for breathing.
Skin Contact:	Wash skin with plenty of water.
Eye Contact:	Rinse eyes with water as a precaution.
Ingestion:	DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water.Get medical attention if any discomfort continues.

Storage
Keep out of reach of children. Keep stock levels to a minimum. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Store in a well-ventilated place. Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
Spillage
See SWP-19. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.
Disposal of Substance & Contaminated Containers

☐	☐	☐	☑	☐
Hazardous Waste	General Waste	Return to Depot	Return to Supplier	Other

Additional Information: Dispose of contents/container in accordance with local regulations.

Is exposure adequately controlled	Yes ☑	No ☐
Risk Rating Following Control Measures		
High ☐	Medium ☐	Low ☑

Assessed by:	Elaine Greaves	Date:	October 2026	Review Date:	April 2028