TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 630-1006RAG

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Teroson PU 9200 BK	Pseudonym	Sealant
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance, Use; infrequent, less than monthly, a few minutes at a time	Location of process being carried out	Customer sites & Toyota workshops

Identify the persons at risk	Team members	✓	Sub-contractors		Customer Team member	✓	Public	

Labelling Elements

 ☐ Explosive

 ☐ Health Hazard

 ☑ Serious Health Hazard

 ☐ Oxidising

 ☐ Corrosive

 ☐ Acute

 ☐ Flammable

 ☐ Environmental

 ☐ Gas

SIGNAL WORD: DANGER

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	✓	☐	☐	☐	☐	☐	✓

Additional Information: Paste

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
✓	✓	✓	✓	☐

Additional Information: Respiratory sensitizer. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Control Measures

Avoid breathing mist/vapours & Dust. Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
Wear protective equipment as listed below.
Avoid contact with skin and eyes.
Do not empty into drains / surface water / ground water.
Observe good hygiene standards at all times. Do not eat, drink or smoke while working.
Wash hands before work breaks and after finishing work.
Use only in well ventilated areas. Wear Suitable breathing mask when there is inadequate ventilation.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes	☐	No	✓

COSHH Risk Assessment:

Part Number: 630-1006RAG

Provide details:

Personal Protective Equipment Required

							
Dust Mask ☐	Visor ☐	Respirator ☐	Goggles ✓	Gloves ✓	Overalls ✓	Footwear ✓	Other ☐

Additional Information:

First Aid Measures	
Inhalation:	Fresh air, oxygen supply, warmth; seek specialist medical attention. Delayed effects possible after inhalation.
Skin Contact:	Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If necessary, see a dermatologist.
Eye Contact:	Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.
Ingestion:	Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Storage

Keep stock levels to as minimum as is practicable. Store in sealed original container protected against moisture and in a cool, dry place. Ensure good ventilation/extraction.
Protect from direct sunlight.
Container must be made airtight after use.

Spillage

See SWP-19. Wear protective equipment. Keep unprotected persons away.
Do not empty into drains / surface water / ground water.

Disposal of Substance & Contaminated Containers

☐	☐	✓	☐	☐
Hazardous Waste	General Waste	Return to Depot	Return to Supplier	Other

Additional Information:

Is exposure adequately controlled	Yes ✓	No ☐

Risk Rating Following Control Measures

High ☐ Medium ☐ Low ✓

Assessed by:	Elaine Greaves	Date:	March 2026	Review Date:	September 2027