TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 6562000400ROC

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	HD Adhesive Grease	Pseudonym	H D Grease
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT maintenance. Use: less than daily for minutes at a time	Location of process being carried out	TMHUK Workshops and Customer Premises

Identify the persons at risk	Team members √	Sub-contractors ☐	Customer Team member ☐	Public ☐

Labelling Elements

 ☐ Explosive

 ☐ Health Hazard

 ☐ Serious Health Hazard

 ☐ Oxidising

 ☐ Corrosive

 ☐ Acute

 ☐ Flammable

 ☐ Environmental

 ☐ Gas

Not Classified

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	☐	☐	☐	☐	☐	√	☐

Additional Information: Green Grease

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
☐	√	√	☐	☐

Additional Information: May be slightly irritating

Control Measures

Read and follow manufacturer's recommendations.
Keep out of reach of children
Wear protective clothing as described below.
Keep away from food, drink and animal feeding stuffs.
Keep container tightly sealed when not in use.
Avoid discharge to the aquatic environment.
Use only in areas where there is adequate ventilation

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.
Wash hands thoroughly after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes ☐	No √

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: 6562000400ROC

Provide details:

Personal Protective Equipment Required							
			 √	 √	 √	 √	
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
			EN 166	EN374			

Additional Information: In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate mask

First Aid Measures	
Inhalation:	Allow affected person to breathe fresh air. Allow the victim to rest.
Skin Contact:	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
Eye Contact:	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists..
Ingestion:	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

Storage

Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Protect from moisture. Keep containers upright. Protect containers from damage. Keep out of reach of children. Storage temperature: 0 – 40 °C

Spillage

See SWP-19. Clear up spills immediately and dispose of waste safely. Collect spillage with a shovel and broom, or similar and reuse, if possible. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Disposal of Substance & Contaminated Containers

Hazardous Waste	General Waste	Depot	Return to Supplier	Other
		√		

Additional Information: Dispose of waste via a licensed waste disposal contractor.

Is exposure adequately controlled	Yes √	No

Risk Rating Following Control Measures		
High	Medium	Low √

Assessed by:	Elaine Greaves	Date:	April 2024	Review Date:	October 2025