TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 7665594

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Ensto Joint Compound SR1	Pseudonym	Grease
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance - For all trucks equipped with a lithium-ion battery system, to provide protection against the oxidation of aluminium surfaces. Use: Less than weekly for minutes at a time	Location of process being carried out	TMHUK Workshops & Customer premises

Identify the persons at risk	Team members √	Sub-contractors ☐	Customer Team member ☐	Public ☐

Labelling Elements

 ☐ Explosive

 ☐ Health Hazard

 ☐ Serious Health Hazard

 ☐ Oxidising

 ☐ Corrosive

 ☐ Acute

 ☐ Flammable

 ☐ Environmental

 ☐ Gas

Product is not classified hazardous.

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	☐	√	☐	☐	√	☐	☐

Additional Information:

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
☐	√	☐	☐	☐

Additional Information: Prolonged or repeated skin contact may irritate the skin and cause dermatitis.

Control Measures

Ensure there is adequate ventilation when using this product.
When using greasing pistol avoid grease penetrating skin. See Safety Message SM05.

Avoid skin contact and inhalation of oil mist. Wear personal protective equipment as detailed below.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes ☐	No √

Provide details:

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: 7665594

Personal Protective Equipment Required							
			 √	 √	 √	 √	
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
			If there is a risk of spashing				

Additional Information:

First Aid Measures	
Inhalation:	If the person exposed to oil mist or vapour has fatigue or nausea, he shall be moved into fresh air. If the symptoms persist, call a physician.
Skin Contact:	Remove contaminated clothing. Wash the skin with plenty of water and soap. If skin irritation persists, call a physician.
Eye Contact:	Rinse immediately with plenty of water, also under the eyelids. Consult a physician.
Ingestion:	DO NOT INDUCE VOMITING. Rinse mouth with water. Call a physician immediately.

Storage
Store at room temperature in the original container. Keep at temperature not exceeding 50°C. Keep tightly closed. The recommended max. period for storage is 5 years.
Spillage
See SWP-19. Gather up spillage and collect in suitable container for disposal. Should not be released into the environment. Prevent product from entering drains.
Disposal of Substance & Contaminated Containers

		√		
Hazardous Waste	General Waste	Depot	Return to Supplier	Other

Additional Information:

Is exposure adequately controlled	Yes √	No
Risk Rating Following Control Measures		
High	Medium	Low √

Assessed by:	Elaine Greaves	Date:	September 2023	Review Date:	May 2025