TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: Automotive Diesel Fuel

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Automotive Diesel Fuel	Pseudonym	Diesel Fuel
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	Fuel for compression ignition diesel engines	Location of process being carried out	Toyota Depots

Identify the persons at risk	Team members √	Sub-contractors ☐	Customer Team member ☐	Public ☐

Labelling Elements

 ☐ Explosive

 ☑ Health Hazard

 ☑ Serious Health Hazard

 ☐ Oxidising

 ☐ Corrosive

 ☐ Acute

 ☐ Flammable

 ☐ Environmental

 ☐ Gas

Signal Word: DANGER

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	√	√	☑	☐	√	☐	☐

Additional Information: Flammable

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
√	√	√	☑	☐

Additional Information: .

Control Measures

Avoid exposure. Do not handle until all safety precautions have been read and understood.
Do not get in eyes, on skin or clothing. Do not breathe vapour or mist. Do not swallow.
Store and use away from heat, sparks, open flame or any other ignition source.
Eating, drinking and smoking should be prohibited where this material is handled, stored and processed.
Wash thoroughly after handling. Remove contaminated clothing and PPE before entering eating areas.
Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area.
In case of fire, use water fog, foam, dry chemical or carbon dioxide extinguisher or spray. Do not use water jet.
Keep away from children.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveillance or monitoring required?	Yes ☐	No √

COSHH Risk Assessment:

Part Number: Automotive Diesel Fuel

Provide details:

Personal Protective Equipment Required							
			 √	 √	 √	 √	
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
Additional Information: Use suitable respiratory protection if ventilation is inadequate.							

First Aid Measures	
Inhalation:	Seek medical attention. Remove to fresh air. If not breathing / irregular breathing provide artificial respiration / oxygen by trained personnel.
Skin Contact:	Immediately flush skin with plenty of water for at least 15 minutes, while removing contaminated clothing and shoes. Drench contaminated clothing before removing. Get medical attention.
Eye Contact:	In case of contact immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from eyeball to ensure thorough rinsing. Check for and remove contact lenses. Seek medical attention.
Ingestion:	Do not induce vomiting. If unconscious place in recovery position and get medical attention immediately.

Storage
Keep out of reach of children. Do not store near heat sources. Protect from freezing and direct sunlight. Store in a dry place. Keep stocks to a minimum
Spillage
See SWP-19. Avoid inhalation of vapors and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas. Avoid discharge into drains. Eliminate all sources of ignition. No smoking, sparks, flames, or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.
Disposal of Substance & Contaminated Containers

		 √		
Hazardous Waste	General Waste	Return to Depot	Return to Supplier	Other

Additional Information: Label as hazardous waste.

Is exposure adequately controlled	Yes √	No

Risk Rating Following Control Measures		
High	Medium	Low √

Assessed by:	Martin Ratcliffe	Date:	Jun 2026	Review Date:	December 2027