TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: SOL-721-2030C

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Floor Paint	Pseudonym	Floor Paint
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	Painting w/shop and warehouse floor areas. No sooner than every 12 months	Location of process being carried out	Internal use only. Toyota Workshop and Warehouse areas

Identify the persons at risk	Team members ✓	Sub-contractors ☐	Customer Team member ☐	Public ☐

Labelling Elements


☐ Explosive


☑ Health Hazard


☐ Serious Health Hazard


☐ Oxidising


☐ Corrosive


☐ Acute


☑ Flammable


☐ Environmental


☐ Gas

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	✓	☐	☐	☐	✓	☐	☐

Additional Information: Flammable Liquid and Vapour

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
✓	✓	✓	✓	☐

Additional Information: May cause drowsiness or dizziness. Allergen.

Control Measures

Read Label before use
Keep out of reach of children
Keep away from heat, sparks, open flames and hot surfaces –No sparking tools to be used. No Smoking.
Avoid breathing vapour or mist, use in well ventilated area. Avoid inhalation of dust from sanding.
Do not allow to enter drains or watercourses.
Eating, drinking and smoking is prohibited in the areas where this product is used.
Wash hands, forearms and face thoroughly after use and before eating, drinking, smoking and using the lavatory.
Wash contaminated clothing before reusing.
Ensure appriate PPE is used (see SWP-32) and that an eyewash station is close by.
This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.









Is health surveilance or monitoring required?	Yes ☐	No ✓

Provide details: Usage not to exceed recommended exposure limits

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: SOL-721-2030C

Personal Protective Equipment Required							
 ☐	 ☐	 ✓	 ✓	 ✓	 ✓	 ✓	 ☐
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
Additional Information:							

First Aid Measures	
Inhalation:	Remove to fresh air. Keep person warm and at rest. Any difficulties with breathing, provide artificial respiration or oxygen by trained personnel.
Skin Contact:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Eye Contact:	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.
Ingestion:	If swallowed, seek medical advice immediately. Keep person warm and at rest. Do NOT induce vomiting

Storage
Observe label Precautions. Store in a dry, cool and well ventilated area and prevent unauthorised access. Keep away from heat, direct sunlight and sources of ignition. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Spillage
Contain and collect spillage using suitable absorbent material – see SWP-19. Clean with detergent, avoid using solvents.
Disposal of Substance & Contaminated Containers

☐ Hazardous Waste	☐ General Waste	✓ Return to Depot	☐ Return to Supplier	☐ Other

Additional Information: Dispose of contents and container in accordance with all local regulations

Is exposure adequately controlled	Yes ✓	No ☐

Risk Rating Following Control Measures		
High ☐	Medium ☐	Low ✓

Assessed by:	Elaine Greaves	Date:	December 2025	Review Date:	June 2027