TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: WA1211

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Fleet Polyurethane	Pseudonym	Textured Black Paint
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance. Use: Daily for less than 1 hour	Location of process being carried out	TMHUK Spray Booth

Identify the persons at risk	Team members √	Sub-contractors ☐	Customer Team member ☐	Public ☐

Labelling Elements


☐ Explosive


√ Health Hazard


√ Serious Health Hazard


☐ Oxidising


☐ Corrosive


☐ Acute


√ Flammable


√ Environmental


☐ Gas

Signal Word: DANGER

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	√	√	☐	☐	√	☐	☐

Additional Information:

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
√	☐	☐	√	☐

Additional Information: Causes damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness.

Control Measures

See SWP-25.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not breathe dust/fume/gas/mist/vapours/spray.
Keep receptacles tightly sealed.
Ensure good ventilation/extraction at the workplace. When spraying the product, use a respiratory protective device.
Prevent formation of aerosols.
Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.
Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product should be placed in purpose-built containers or in metal containers with tight-fitting self-closing lids, removed from the workplace at the end of each working day and disposed of.
This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes ☐	No √

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: WA1211

Provide details:

Personal Protective Equipment Required							
		 √	 √	 √	 √	 √	
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other

Additional Information:

First Aid Measures	
Inhalation:	Supply fresh air; consult doctor in case of complaints.
Skin Contact:	Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Immediately rinse with water.
Eye Contact:	Rinse opened eye for several minutes under running water.
Ingestion:	Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

Storage

Keep receptacle tightly sealed and in a well-ventilated place.
Keep away from heat.

Spillage

See SWP-19. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to below. Ensure adequate ventilation.

Disposal of Substance & Contaminated Containers

Hazardous Waste	General Waste	Depot	Return to Supplier	Other
		√		

Additional Information:

Is exposure adequately controlled	Yes √	No

Risk Rating Following Control Measures

High	Medium	Low
		√

Assessed by:	Elaine Greaves	Date:	February 2024	Review Date:	August 2026