Toyota Material Handling UK Limited - Orange Generation 7 Spray Paint 400ml Aerosols 130014

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
Issue date: 16/01/2026 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Product name	:	Toyota Material Handling UK Limited - Orange Generation 7 Spray Paint 400ml Aerosols 130014
Product code	:	937
Type of product	:	Spray Paint
Vaporizer	:	Aerosol
Product group	:	End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category	:	Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Specialised Chemicals Ltd
Tollemache Road South Spittlegate Level Industrial Estate
NG31 7UH Grantham – Lincolnshire
United Kingdom
T 01476 567615
technical@specialisedchemicals.com - www.specialisedchemicals.com

1.4. Emergency telephone number

Emergency number	:	01476 567615

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GB CLP (SI 2019:720 as amended)

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Repeated exposure, Category 2	H373

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Labelling according to GB CLP (SI 2019:720 as amended)

Hazard pictograms (GHS UK) :



GHS02 GHS07 GHS08

Signal word (GHS UK) : Danger

Contains : xylene; 1-methoxypropan-2-ol; Acetone

Hazard statements (GHS UK) : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS UK) : P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P260 - Do not breathe vapours, spray.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing, face protection, eye protection.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

EUH-statements (GHS UK) : EUH208 - Contains 2-Ethylhexanoic acid cobalt(2+) salt; Cobaltous octoate. May produce an allergic reaction.

2.3. Other hazards

Results of PBT and vPvB assessment

Component	
Substance(s) not meeting the PBT criteria of UK REACH regulation, in accordance with Annex XIII	xylene (1330-20-7), ethylbenzene (100-41-4), 1-methoxypropan-2-ol (107-98-2), Cobalt bis(2-ethylhexanoate) (136-52-7), Acetone (67-64-1)
Substance(s) not meeting the vPvB criteria of UK REACH regulation, in accordance with Annex XIII	xylene (1330-20-7), ethylbenzene (100-41-4), 1-methoxypropan-2-ol (107-98-2), Cobalt bis(2-ethylhexanoate) (136-52-7), Acetone (67-64-1)

Results of Endocrine Disruptor assessment

Component	
Substance(s) not considered as endocrine disrupting. They are not included in the list established in accordance with Article 59(1) of UK REACH for having endocrine disrupting properties, nor identified as having endocrine disrupting properties in accordance with the criteria set out in GB BPR and GB PPP	Acetone(67-64-1), xylene(1330-20-7), 1-methoxypropan-2-ol(107-98-2), ethylbenzene(100-41-4), Cobalt bis(2-ethylhexanoate)(136-52-7)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to GB CLP (SI 2019:720 as amended)
Acetone substance with workplace exposure limit(s)	CAS-No.: 67-64-1 EC-No.: 200-662-2 UK Index-No.: 606-001-00-8	≥ 10 – < 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
xylene substance with workplace exposure limit(s)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 UK Index-No.: 601-022-00-9	≥ 10 – < 30	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=11 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
1-methoxypropan-2-ol substance with workplace exposure limit(s)	CAS-No.: 107-98-2 EC-No.: 203-539-1 UK Index-No.: 603-064-00-3	≥ 1 – < 5	Flam. Liq. 3, H226 STOT SE 3, H336
ethylbenzene substance with workplace exposure limit(s)	CAS-No.: 100-41-4 EC-No.: 202-849-4 UK Index-No.: 601-023-00-4	≥ 1 – < 5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 (ATE=11 mg/l/4h) STOT RE 2, H373 Asp. Tox. 1, H304
Cobalt bis(2-ethylhexanoate)	CAS-No.: 136-52-7 EC-No.: 205-250-6	< 1	Eye Irrit. 2, H319 Skin Sens. 1A, H317 Repr. 1B, H360F STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.
Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

Self protection of the first-aider : First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : Irritation.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling	:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	:	Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Keep in a cool, well-ventilated place away from heat.
Storage conditions	:	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Packaging materials	:	Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

xylene (1330-20-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Xylene
WEL TWA (OEL TWA)	220 mg/m³ o-,m-,p- or mixed isomers
	50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m³ o-,m-,p- or mixed isomers
	100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

ethylbenzene (100-41-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Ethylbenzene
WEL TWA (OEL TWA)	441 mg/m³
	100 ppm
WEL STEL (OEL STEL)	552 mg/m³
	125 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

1-methoxypropan-2-ol (107-98-2)	
United Kingdom - Occupational Exposure Limits	
Local name	1-Methoxypropan-2-ol
WEL TWA (OEL TWA)	375 mg/m³
	100 ppm
WEL STEL (OEL STEL)	560 mg/m³
	150 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Acetone (67-64-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA)	1210 mg/m³
	500 ppm
WEL STEL (OEL STEL)	3620 mg/m³
	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:
Wear recommended personal protective equipment.
Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Safety glasses

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Appearance	:	Aerosol.
Colour	:	orange.
Odour	:	solvent-like.
Odour threshold	:	Not available
pH	:	Not available
Melting point	:	Not applicable
Freezing point	:	Not available
Boiling point	:	-25 (-25 – 215) °C
Flash point	:	-41 °C
Flammability	:	Extremely flammable aerosol.
Lower explosion limit	:	0.8 vol %
Upper explosion limit	:	32 vol %
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available
Relative vapour density at 20°C	:	Not available
Relative density	:	0.79
Density	:	Not available
Solubility	:	Insoluble.
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Auto-ignition temperature	:	226 °C
Decomposition temperature	:	Not available
Viscosity, kinematic	:	Not available
Explosive properties	:	Pressurised container: May burst if heated.

9.2. Other information

Particle characteristics	:	Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg Source: ECHA
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	5922 ppm

ethylbenzene (100-41-4)	
LD50 oral rat	≈ 3500 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 20000 mg/kg Source: ECHA
LC50 Inhalation - Rat [ppm]	4000 ppm

1-methoxypropan-2-ol (107-98-2)	
LD50 oral rat	4016 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 dermal rabbit	> 2000 mg/kg Source: ECHA

Cobalt bis(2-ethylhexanoate) (136-52-7)	
LD50 oral rat	3129 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 2000 mg/kg

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

xylene (1330-20-7)	
IARC group	3 - Not classifiable

ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

Acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male

STOT-single exposure : May cause drowsiness or dizziness.

xylene (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.

1-methoxypropan-2-ol (107-98-2)	
STOT-single exposure	May cause drowsiness or dizziness.

Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

xylene (1330-20-7)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs (hearing organs) through prolonged or repeated exposure.

1-methoxypropan-2-ol (107-98-2)	
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Cobalt bis(2-ethylhexanoate) (136-52-7)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.31 mg/l air Animal: rat
NOAEL (oral, rat, 90 days)	3 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

Toyota Material Handling UK Limited - Orange Generation 7 Spray Paint 400ml Aerosols 130014	
Vaporizer	Aerosol

1-methoxypropan-2-ol (107-98-2)	
Viscosity, kinematic	1.848 mm²/s

Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short–term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long–term (chronic) : Not classified (Based on available data, the classification criteria are not met)

xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Source: ECHA
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

1-methoxypropan-2-ol (107-98-2)	
LC50 - Fish [1]	≥ 1000 mg/l Source: EHCA
EC50 - Crustacea [1]	21100 – 25900 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	2954 mg/l Test organisms (species): other aquatic crustacea:
EC50 72h - Algae [1]	> 500 mg/l Source: EHCA

Cobalt bis(2-ethylhexanoate) (136-52-7)	
LC50 - Fish [1]	1.512 mg/l Source: ECHA
EC50 - Crustacea [1]	5.89 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	0.654 mg/l Source: ECHA registration data

Acetone (67-64-1)	
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Toyota Material Handling UK Limited - Orange Generation 7 Spray Paint 400ml Aerosols 130014	
Persistence and degradability	Not rapidly degradable

xylene (1330-20-7)	
Persistence and degradability	Not rapidly degradable

ethylbenzene (100-41-4)	
Persistence and degradability	Not rapidly degradable

1-methoxypropan-2-ol (107-98-2)	
Persistence and degradability	Not rapidly degradable

Cobalt bis(2-ethylhexanoate) (136-52-7)	
Persistence and degradability	Not rapidly degradable

Acetone (67-64-1)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

xylene (1330-20-7)	
Partition coefficient n-octanol/water (Log Pow)	3.15 Source: HSDB

ethylbenzene (100-41-4)	
Partition coefficient n-octanol/water (Log Pow)	3.15 Source: HSDB

1-methoxypropan-2-ol (107-98-2)	
Partition coefficient n-octanol/water (Log Pow)	-0.49 Source: HSDB

Cobalt bis(2-ethylhexanoate) (136-52-7)	
Partition coefficient n-octanol/water (Log Pow)	2.96 Source: ECHA

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component	
xylene (1330-20-7)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII
ethylbenzene (100-41-4)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII
1-methoxypropan-2-ol (107-98-2)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII
Cobalt bis(2-ethylhexanoate) (136-52-7)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII
Acetone (67-64-1)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII

12.6. Other adverse effects

Ozone : Not classified (Based on available data, the classification criteria are not met)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.

HP Code : HP3 - “Flammable:”
– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
HP5 - “Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:” waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
HP4 - “Irritant – skin irritation and eye damage:” waste which on application can cause skin irritation or damage to the eye.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F
Special provisions (ADR) : 190, 327, 344, 625
Limited quantities (ADR) : 1l
Excepted quantities (ADR) : E0

Packing instructions (ADR)	:	P207, LP200
Special packing provisions (ADR)	:	PP87, RR6, L2
Mixed packing provisions (ADR)	:	MP9
Transport category (ADR)	:	2
Special provisions for carriage - Packages (ADR)	:	V14
Special provisions for carriage - Loading, unloading and handling (ADR)	:	CV9, CV12
Special provisions for carriage - Operation (ADR)	:	S2
Tunnel restriction code (ADR)	:	D

Transport by sea

Special provisions (IMDG)	:	63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	:	SP277
Excepted quantities (IMDG)	:	E0
Packing instructions (IMDG)	:	P207, LP200
Special packing provisions (IMDG)	:	PP87, L2
EmS-No. (Fire)	:	F-D
EmS-No. (Spillage)	:	S-U
Stowage category (IMDG)	:	None
Stowage and handling (IMDG)	:	SW1, SW22
Segregation (IMDG)	:	SG69

Air transport

PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Y203
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
Special provisions (IATA)	:	A145, A167, A802
ERG code (IATA)	:	10L

Inland waterway transport

Classification code (ADN)	:	5F
Special provisions (ADN)	:	190, 327, 344, 625
Limited quantities (ADN)	:	1 L
Excepted quantities (ADN)	:	E0
Equipment required (ADN)	:	PP, EX, A
Ventilation (ADN)	:	VE01, VE04
Number of blue cones/lights (ADN)	:	1

Rail transport

Classification code (RID)	:	5F
Special provisions (RID)	:	190, 327, 344, 625
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E0
Packing instructions (RID)	:	P207, LP200
Special packing provisions (RID)	:	PP87, RR6, L2
Mixed packing provisions (RID)	:	MP9
Transport category (RID)	:	2
Special provisions for carriage – Packages (RID)	:	W14
Special provisions for carriage - Loading, unloading and handling (RID)	:	CW9, CW12
Colis express (express parcels) (RID)	:	CE2
Hazard identification number (RID)	:	23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. National regulations

UK REACH Annex XVII (Restriction List)

This product contains no substance(s) listed on UK REACH Annex XVII (Restriction List) equal to or above the level of SDS disclosure

UK REACH Annex XIV (Authorisation List)

This product contains no substance(s) listed on UK REACH Annex XIV (Authorisation List) equal to or above the 0.1% level of disclosure

UK REACH Candidate List (SVHC)

This product contains no substance(s) listed on the UK REACH Candidate List (SVHC) above the 0.1% level of disclosure

GB PIC Regulation (Prior Informed Consent)

This product contains no substance(s) listed on the GB PIC List equal to or above the level of SDS disclosure

POP Regulation (Persistent Organic Pollutants)

This product contains no substance(s) listed on the GB POP List equal to or above the level of SDS disclosure

Ozone Regulation (S.I. No. 168 of 2015)

This product contains no substance(s) listed on the GB Ozone Depletion List equal to or above the level of SDS disclosure

Control of Poisons and Explosives Precursors Act

This product contains no substance(s) listed as a reportable poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure
This product contains no substance(s) listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure
This product contains substance(s) listed on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure: Acetone - 67-64-1
This substance is not listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations

Drug Precursors Regulation (EC 273/2004)

This product contains substance(s) listed on the GB Drug Precursors List equal to or above the level of SDS disclosure (Acetone - 67-64-1)

15.1.2. Other Information

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
BS EN	British Standard
CAS-No.	Chemical Abstract Service number
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level

Abbreviations and acronyms:	
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 1B	Reproductive toxicity, Category 1B

Full text of H- and EUH-statements:	
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360F	May damage fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Cobalt bis(2-ethylhexanoate) (136-52-7) (SUB). May produce an allergic reaction.

Safety Data Sheet (SDS), UK

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.