SAFETY DATA SHEET
MASTER TOYOTA ORANGE 756065

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MASTER TOYOTA ORANGE 756065

Product number 27392

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Touch-up paint for forklifts

1.3. Details of the supplier of the safety data sheet

Supplier

Spray Master AB
Fabriksvägen 5
Box 1050
S-186 26 Vallentuna
Sweden
Tel: +46 (8) 505 133 00
Fax: +46 (8) 505 133 01
Info@spraymaster.se

1.4. Emergency telephone number

National emergency telephone number 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH208 Contains ETHYL METHYL KETOXIME, COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.

MASTER TOYOTA ORANGE 756065

Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/ container in accordance with national regulations. P102 Keep out of reach of children.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	ETHYL ACETATE, Naphtha (petroleum), hydrotreated heavy (<0,1%Benzen), 1-METHOXY-2-PROPANOL
Supplementary precautionary statements	P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/ doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/ attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ETHYL ACETATE **25-35%**

CAS number: 141-78-6 | EC number: 205-500-4 | REACH registration number: 01-2119475103-46

Classification
Flam. Liq. 2 - H225
Eye Irrit. 2 - H319
STOT SE 3 - H336

DIMETHYL ETHER **15-24.9%**

CAS number: 115-10-6 | EC number: 204-065-8 | REACH registration number: 01-2119472128-37

Classification
Flam. Gas 1 - H220
Press. Gas, Compressed - H280

MASTER TOYOTA ORANGE 756065

Naphtha (petroleum), hydrotreated heavy (<0,1%Benzen) **10-15%**

CAS number: 64742-48-9 EC number: 265-150-3

Classification
Flam. Liq. 3 - H226
STOT SE 3 - H336
Asp. Tox. 1 - H304

1-METHOXY-2-PROPANOL **5-7.49%**

CAS number: 107-98-2 EC number: 203-539-1 REACH registration number: 01-2119457435-35-0000

Classification
Flam. Liq. 3 - H226
STOT SE 3 - H336

BUTANE **5-7.49%**

CAS number: 106-97-8 EC number: 203-448-7 REACH registration number: 01-2119474691-32

Classification
Flam. Gas 1 - H220
Press. Gas, Compressed - H280

PROPANE **5-7.49%**

CAS number: 74-98-6 EC number: 200-827-9 REACH registration number: 01-2119486944-21

Classification
Flam. Gas 1 - H220
Press. Gas, Compressed - H280

ETHYL METHYL KETOXIME **<0,5%**

CAS number: 96-29-7 EC number: 202-496-6 REACH registration number: 01-2119539477-28-0000

Classification
Acute Tox. 4 - H312
Eye Dam. 1 - H318
Skin Sens. 1 - H317
Carc. 2 - H351

MASTER TOYOTA ORANGE 756065

COBALT BIS(2-ETHYLHEXANOATE)		**<0,2**
CAS number: 136-52-7	EC number: 205-250-6	REACH registration number: 01-2119524678-29-0000
M factor (Acute) = 1		

Classification
Eye Irrit. 2 - H319
Skin Sens. 1 - H317
Repr. 2 - H361
Aquatic Acute 1 - H400
Aquatic Chronic 2 - H411

PENTANE		**<0.099%**
CAS number: 109-66-0	EC number: 203-692-4	REACH registration number: 01-2119459286-30-0000

Classification
Flam. Liq. 2 - H225
STOT SE 3 - H336
Asp. Tox. 1 - H304
Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

Composition comments The Naphthas contains less than 0.1% benzene, which means that they are not classified as mutagenic or carcinogenic.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

Ingestion Drink a few glasses of water or milk. DO NOT induce vomiting. Get medical attention immediately.

Skin contact Wash skin thoroughly with soap and water.

Eye contact Rinse with water. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information Solvent abuse can kill instantly.

Inhalation May cause drowsiness or dizziness. Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Skin contact Repeated exposure may cause skin dryness or cracking. May cause sensitisation or allergic reactions in sensitive individuals.

Eye contact Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

MASTER TOYOTA ORANGE 756065

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Extremely flammable.

5.3. Advice for firefighters

Protective actions during firefighting Containers close to fire should be removed or cooled with water.

Special protective equipment for firefighters Wear chemical protective suit. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Large Spillages: Contain and absorb spillage with sand, earth or other non-combustible material. Small Spillages: Wipe away with paper or textile fabric.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Protect against direct sunlight. Avoid eating, drinking and smoking when using the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep container dry.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm
Short-term exposure limit (15-minute): WEL 400 ppm

DIMETHYL ETHER

MASTER TOYOTA ORANGE 756065

Long-term exposure limit (8-hour TWA): WEL 400 ppm 766 mg/m³
Short-term exposure limit (15-minute): WEL 500 ppm 958 mg/m³

1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m³
Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m³
Sk

PENTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1800 mg/m³
Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit
Sk = Can be absorbed through the skin.

DIMETHYL ETHER (CAS: 115-10-6)

DNEL	Professional - Inhalation; Long term systemic effects: 1894 mg/m³ Consumer - Inhalation; Long term systemic effects: 471 mg/m³
PNEC	- Fresh water; 0,155 mg/l - Marine water; 0,016 mg/l - Sediment (Freshwater); 0,681 mg/kg - Sediment (Marinewater); 0,069 mg/kg - Soil; 0,045 mg/kg

PENTANE (CAS: 109-66-0)

PNEC	- water; 0,027 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls	All handling should only take place in well-ventilated areas.
Eye/face protection	The following protection should be worn: Chemical splash goggles.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber.
Other skin and body protection	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Wear apron or protective clothing in case of contact.
Hygiene measures	Wash at the end of each work shift and before eating, smoking and using the toilet.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P3.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Orange.

MASTER TOYOTA ORANGE 756065

Odour	Solvent.
Odour threshold	Not determined.
pH	Not determined.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	Technical impossibility to obtain the data.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Other flammability	Not determined.
Vapour pressure	250-450 kPa @ 20°C
Vapour density	Not determined.
Relative density	~0,85 @ °C
Bulk density	Not determined.
Solubility(ies)	Organic solvents.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not determined.
Explosive properties	Not determined.
Explosive under the influence of a flame	Yes
Oxidising properties	Not determined.

9.2. Other information

Other information	Not relevant.
Refractive index	Not determined.
Particle size	Not determined.
Molecular weight	Not determined.
Volatility	Highly volatile.
Saturation concentration	Not determined.
Critical temperature	Not determined.
Volatile organic compound	Category: special finishes. VOC limit: 840 g/l This product contains a maximum VOC content of 725 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

MASTER TOYOTA ORANGE 756065

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Not known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No data is available regarding the preparation it self.

Acute toxicity - oral

Notes (oral LD_{50}) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD_{50}) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC_{50}) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Does not contain any substances known to be mutagenic.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Reproductive toxicity

Reproductive toxicity - fertility Does not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

MASTER TOYOTA ORANGE 756065

Specific target organ toxicity - repeated exposure

STOT - repeated exposure	Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard	Based on available data the classification criteria are not met. Aerosol dispenser. The mist is fine, a pool may not be formed.
General information	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	May cause drowsiness or dizziness. Vapours have a narcotic effect. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. May cause respiratory system irritation.
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Skin contact	Repeated exposure may cause skin dryness or cracking. May cause sensitisation or allergic reactions in sensitive individuals.
Eye contact	Irritation of eyes and mucous membranes.
Acute and chronic health hazards	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Nausea, vomiting. Headache.

Toxicological information on ingredients.

ETHYL ACETATE

Acute toxicity - oral

Acute toxicity oral (LD_{50} mg/kg)	5,620.0
Species	Rat

Acute toxicity - dermal

Acute toxicity dermal (LD_{50} mg/kg)	18,000.0
Species	Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation (LC_{50} vapours mg/l)	5.77
Species	Rat
ATE inhalation (vapours mg/l)	5.77

DIMETHYL ETHER

Acute toxicity - oral

Notes (oral LD_{50})	Not applicable.

Acute toxicity - dermal

Notes (dermal LD_{50})	Not applicable.

MASTER TOYOTA ORANGE 756065

Skin contact	Risk of frostbite.

BUTANE

Acute toxicity - oral	
Notes (oral LD_{50})	Not applicable.
Acute toxicity - dermal	
Notes (dermal LD_{50})	Not applicable.
Acute toxicity - inhalation	
Acute toxicity inhalation (LC_{50} vapours mg/l)	20.0
Notes (inhalation LC_{50})	

PROPANE

Acute toxicity - oral	
Notes (oral LD_{50})	Not applicable.
Acute toxicity - dermal	
Notes (dermal LD_{50})	Not applicable.
Acute toxicity - inhalation	
Acute toxicity inhalation (LC_{50} vapours mg/l)	20.0
Notes (inhalation LC_{50})	

ETHYL METHYL KETOXIME

Acute toxicity - oral	
Acute toxicity oral (LD_{50} mg/kg)	930.0
Species	Rat
Acute toxicity - inhalation	
Acute toxicity inhalation (LC_{50} vapours mg/l)	20.0
Species	Rat
ATE inhalation (vapours mg/l)	20.0

PENTANE

Acute toxicity - oral	
Acute toxicity oral (LD_{50} mg/kg)	400.0
Species	Rat
Acute toxicity - dermal	

MASTER TOYOTA ORANGE 756065

Acute toxicity dermal (LD_{50} mg/kg)	3,000.0
Species	Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation (LC_{50} vapours mg/l)	364.0
Species	Rat
ATE inhalation (vapours mg/l)	364.0

SECTION 12: Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

12.1. Toxicity

Toxicity No data is available regarding the preparation itself.

Ecological information on ingredients.

ETHYL ACETATE

Acute toxicity - fish	LC50, 96 hours: 230 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EC_{50}, 48 hours: 154 - 717 mg/l, Daphnia magna EC_{50}, 48 hours: mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC_{50}, 48 hours: 3300 mg/l, Scenedesmus subspicatus

DIMETHYL ETHER

Acute toxicity - fish	LC50, 96 hours: > 4.1 mg/l, Poecilia reticulata (Guppy)
Acute toxicity - aquatic invertebrates	EC_{50}, 48 hours: > 4.4 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC_{50}, 96 hours: 154.9 mg/l, Freshwater algae

Naphtha (petroleum), hydrotreated heavy (<0,1%Benzen)

Acute toxicity - fish	LC_{50}, 96 hours: 2200 mg/l, Pimephales promelas (Fat-head Minnow)

BUTANE

Acute toxicity - fish	Highly volatile. LC50, 96 hours: 24.11 mg/l,
Acute toxicity - aquatic invertebrates	Highly volatile. EC_{50}, 48 hours: 14.22 mg/l, Daphnia magna

PROPANE

Acute toxicity - aquatic invertebrates	Highly volatile. EC_{50}, 48 hours: 27.14 mg/l,

MASTER TOYOTA ORANGE 756065

Acute toxicity - aquatic plants	, : ,

ETHYL METHYL KETOXIME

Acute toxicity - fish	LC50, 96 hours: 760 mg/l, Poecilia reticulata (Guppy)
Acute toxicity - aquatic invertebrates	EC_{50}, 48 hours: > 500 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC_{50}, 72 hours: 83 mg/l, Scenedesmus subspicatus

COBALT BIS(2-ETHYLHEXANOATE)

Acute aquatic toxicity

LE(C)$_{50}$	0.1 < L(E)C50 ≤ 1
M factor (Acute)	1

PENTANE

Acute toxicity - fish	LC50, 96 hours: 4,26 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC_{50}, 48 hours: 2,7-9,1 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC_{50}, 72 hours: 7,51 mg/l, Selenastrum capricornutum

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients.

ETHYL ACETATE

Persistence and degradability	Readily biodegradable.

DIMETHYL ETHER

Persistence and degradability	The product is not readily biodegradable.

Naphtha (petroleum), hydrotreated heavy (<0,1%Benzen)

Biodegradation	- Degradation 70%: 28 days OECD 301F

BUTANE

Persistence and degradability	The product is readily biodegradable.

PROPANE

MASTER TOYOTA ORANGE 756065

Persistence and degradability The product is readily biodegradable.

Biodegradation Water - :

ETHYL METHYL KETOXIME

Biodegradation - Degradation (%) 70: 14 days
OECD 301C

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

DIMETHYL ETHER

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

BUTANE

Bioaccumulative potential The product is not bioaccumulating.

PROPANE

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient :

ETHYL METHYL KETOXIME

Bioaccumulative potential BCF: 5,8,

Partition coefficient log Pow: 0,63

PENTANE

Bioaccumulative potential BCF: 171,

Partition coefficient log Pow: 3,4

12.4. Mobility in soil

Mobility No information available

Ecological information on ingredients.

DIMETHYL ETHER

Adsorption/desorption coefficient Water - Koc: ~ 7.759 @ °C

BUTANE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

PROPANE

MASTER TOYOTA ORANGE 756065

Mobility	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects	No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	The manufacturer of this product complies with the rules and regulations of the European Parliament and Council Directive 94/62/EC of 20 December 1994 on packaging and packaging waste, by paying packaging fees for disposal and recycling of packaging waste.
Disposal methods	The plastic lid and valve are sorted as plastic. Empty aerosols are sorted as scrap metal. Residues and non empty containers should be taken care of as hazardous waste according to local and national regulations.
Waste class	Non empty containers: EWC code 08 01 11* Empty containers: EWC code 15 01 04

SECTION 14: Transport information

General	Aerosols may be carried domestically as limited quantities (1L) as long as each package does not exceed 30 kg in cardboard boxes or 20 kg on trays with shrink- or stretch wrapping. Each package shall be marked with diamond-shaped area, the top and bottom part is black, surrounded by a line that measures at least 100 mm x 100 mm.

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1

MASTER TOYOTA ORANGE 756065

ADN class 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations COUNCIL DIRECTIVE of may 1975 on the approximation of the laws of the Member States relating to aerosol dispensers.

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information A review of safety data sheet with staff to manage the product recommended.

Classification procedures according to Regulation (EC) 1272/2008 Asp. Tox. 1 - H304: Based on available data the classification criteria are not met. Aerosol dispenser. The mist is fine, a pool may not be formed.

Issued by Björkstedt

Revision date 13/11/2017

Revision 3

Supersedes date 10/09/2015

MASTER TOYOTA ORANGE 756065

Hazard statements in full

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: may burst if heated
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
EUH208 Contains ETHYL METHYL KETOXIME, COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.