SAFETY DATA SHEET

Mirror Image

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

Part No: SDS10109 - Mirror Image Polish

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Mirror Image

Product number 140-23

UFI UFI: 9WYV-V05J-300Q-1C2T

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product. - Polish.

Uses advised against This product is not recommended for any industrial, professional or consumer use other than the Identified uses above. For professional use only.

1.3. Details of the supplier of the safety data sheet

Supplier
Autosmart International Ltd
Lynn Lane
Shenstone, nr Lichfield
Staffordshire. WS14 0DH
England
www.autosmartinternational.com
Tel: +44 (0) 1543 481616 (09:00 - 17:00)
SHREQ@autosmart.co.uk

Contact person Mr. Russell Butler

Manufacturer
Autosmart International Ltd.
Lynn Lane
Shenstone, nr Lichfield
Staffordshire WS14 0DH
Great Britain
www.autosmartinternational.com
Tel: +44 (0) 1543 481616 (09:00 - 17:00)
Fax: +44 (0) 1543 481549 (09:00 - 17:00)
info@autosmartinternational.com

1.4. Emergency telephone number

Emergency telephone
NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident), Call NCEC at +44 1865 407333 (24Hrs UK)
when calling please quote "AUTOSMART 29003-NCEC"

If you urgently need medical help or advice but it's not a life-threatening situation, call 111 free from any phone to speak to an NHS adviser. The 24-hour NHS 111 service can give you healthcare advice or direct you to the local service that can help you best.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Mirror Image

Classification (SI 2019 No. 720)

Physical hazards	Not Classified
Health hazards	STOT SE 3 - H336
Environmental hazards	Aquatic Chronic 3 - H412

2.2. Label elements

Hazard pictograms



Signal word	Warning
Hazard statements	H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P273 Avoid release to the environment. P280 Wear protective gloves. P261 Avoid breathing vapours. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
UFI	UFI: 9WYV-V05J-300Q-1C2T
Contains	Naphtha (petroleum), hydrotreated heavy
Detergent labelling	< 5% cationic surfactants, < 5% non-ionic surfactants, < 5% perfumes

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Naphtha (petroleum), hydrotreated heavy **20<30%**

CAS number: 64742-48-9 EC number: 919-857-5

Substance with a Community workplace exposure limit.

Classification
Flam. Liq. 3 - H226
STOT SE 3 - H336
Asp. Tox. 1 - H304

Anhydrous Aluminium Silicate **3<5%**

CAS number: 92704-41-1 EC number: 296-473-8

Substance with a Community workplace exposure limit.

Classification
Not Classified

Mirror Image

Aluminium Silicate **2<3%**

CAS number: 1332-58-7 EC number: 310-194-1

Substance with a Community workplace exposure limit.

Classification
Not Classified

Paraffin Wax 150/155 **1.25<1.5**

CAS number: 8002-74-2 EC number: 232-315-6

Substance with a Community workplace exposure limit.

Classification
Not Classified

2,2'-(Octadec-9-enylimino)bisethanol **0.5<0.7%**

CAS number: 25307-17-9 EC number: 246-807-3

M factor (Acute) = 10 M factor (Chronic) = 1

Classification
Acute Tox. 4 - H302
Skin Corr. 1B - H314
Eye Dam. 1 - H318
Aquatic Acute 1 - H400
Aquatic Chronic 1 - H410

Dicocodimethylammonium chloride **0.2<0.5%**

CAS number: 61789-77-3 EC number: 263-087-6

M factor (Acute) = 1

Classification
Acute Tox. 4 - H302
Skin Corr. 1B - H314
Eye Dam. 1 - H318
Aquatic Acute 1 - H400
Aquatic Chronic 2 - H411

Diiron Trioxide **0.1<0.2%**

CAS number: 1309-37-1 EC number: 215-168-2

Substance with a Community workplace exposure limit.

Classification
Not Classified

Mirror Image

Titanium Dioxide **0.1<0.2%**

CAS number: 13463-67-7 EC number: 236-675-5

Substance with a Community workplace exposure limit.

Classification
Not Classified

propan-2-ol **0.1<0.2%**

CAS number: 67-63-0 EC number: 200-661-7

Substance with a Community workplace exposure limit.

Classification
Flam. Liq. 2 - H225
Eye Irrit. 2 - H319
STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

Skin contact Rinse with water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Mirror Image

Inhalation A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.

Ingestion Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid inhalation of dust and vapours. Use suitable respiratory protection if ventilation is inadequate.

6.2. Environmental precautions

Mirror Image

Environmental precautions Immiscible with water. Aquatic toxicity is unlikely to occur. However, large or frequent spills may have hazardous effects on the environment. Absorb spillage with non-combustible, absorbent material. Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Mirror Image

Naphtha (petroleum), hydrotreated heavy

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m³
Short-term exposure limit (15-minute): WEL

Anhydrous Aluminium Silicate

Long-term exposure limit (8-hour TWA): WEL 2 mg/m³

Aluminium Silicate

Long-term exposure limit (8-hour TWA): WEL 2 mg/m³ respirable dust

Paraffin Wax 150/155

Long-term exposure limit (8-hour TWA): WEL 2 mg/m³ fume
Short-term exposure limit (15-minute): WEL 6 mg/m³ fume

Diiron Trioxide

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust
Long-term exposure limit (8-hour TWA): WEL 5 mg/m³ fume
Short-term exposure limit (15-minute): WEL 10 mg/m³ fume
as Fe
Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Titanium Dioxide

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust
Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

propan-2-ol

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³
Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³
WEL = Workplace Exposure Limit.

Naphtha (petroleum), hydrotreated heavy (CAS: 64742-48-9)

DNEL	Industry - Dermal; Long term : 208 mg/kg/day Industry - Inhalation; Long term : 871 mg/kg/day Consumer - Dermal; Long term : 125 mg/kg/day Consumer - Inhalation; Long term : 185 mg/kg/day Consumer - Oral; Long term : 125 mg/kg/day

2,2'-(Octadec-9-enylimino)bisethanol (CAS: 25307-17-9)

Ingredient comments	No exposure limits known for ingredient(s).
DNEL	Workers - Dermal; Long term systemic effects: 0.25 mg/kg/day Workers - Inhalation; Long term systemic effects: 1.76 mg/m³ Consumer - Dermal; Long term systemic effects: 0.179 mg/kg/day Consumer - Inhalation; Long term systemic effects: 0.621 mg/m³ Consumer - Oral; Long term systemic effects: 0.179 mg/kg/day
PNEC	- Fresh water; 0.000214 mg/l - marine water; 0.000021 mg/l - STP; 1.5 mg/l - Sediment (Freshwater); 1.692 mg/kg - Sediment (Marinewater); 0.1692 mg/kg - Soil; 5 mg/kg

Dicocodimethylammonium chloride (CAS: 61789-77-3)

Mirror Image

Ingredient comments	No exposure limits known for ingredient(s).
DNEL	Professional - Dermal; Long term systemic effects: 12.75 mg/kg/day Industry - Inhalation; Long term systemic effects: 27 mg/m³ Consumer - Dermal; Long term systemic effects: 7.65 mg/kg/day Consumer - Inhalation; Long term systemic effects: 8 mg/m³ Consumer - Oral; Long term systemic effects: 2.3 mg/kg/day
PNEC	- Fresh water; 0.013 mg/l - marine water; 0.0013 mg/l - STP; 1.2 - Sediment (Freshwater); 8.8 mg/kg - Sediment (Marinewater); 0.88 mg/kg - Soil; 7 mg/kg

propan-2-ol (CAS: 67-63-0)

DNEL	Industry - Inhalation; Long term systemic effects: 500 mg/m³ Consumer - Dermal; Long term systemic effects: 319 mg/kg/day Consumer - Oral; Long term systemic effects: 26 mg/kg/day Consumer - Inhalation; Long term systemic effects: 89 mg/m³ Industry - Dermal; Long term systemic effects: 888 mg/kg/day
PNEC	- Fresh water; 140.9 mg/l - marine water; 140.9 mg/l - Intermittent release; 140.9 mg/l - Sediment (Freshwater); 552 mg/kg - Sediment (Marinewater); 552 mg/kg - STP; 2251 mg/l - Soil; 28 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment that provides appropriate eye and face protection should be worn. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Mirror Image

Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. When used with mixtures, the protection time of gloves cannot be accurately estimated. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber. Thickness: > 0.2 mm The selected gloves should have a breakthrough time of at least 0.5 hours. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application. Use thin cotton gloves inside natural rubber gloves if there is an allergy risk to natural rubber.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'UKCA'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges suitable for intended use should be used. Full face mask respirators with replaceable filter cartridges suitable for intended use should be used. Half mask and quarter mask respirators with replaceable filter cartridges suitable for intended use should be used.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid. Liquid.
Colour	Yellow.
Odour	Pleasant, agreeable.
Odour threshold	Not available.
pH	pH (concentrated solution): ~ 7.0
Initial boiling point and range	Not available.
Flash point	> 62°C Closed cup.

Mirror Image

Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Other flammability	This product does not sustain combustion, according to the sustained combustibility test L.2, Part III, section 32 of the UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	~ 0.965 @ (20°C)°C
Solubility(ies)	Insoluble in water. Miscible with the following materials: Hydrocarbons.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not available. Kinematic viscosity > 20.5 mm²/s.
Oxidising properties	Does not meet the criteria for classification as oxidising.
Comments	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.

9.2. Other information

Volatile organic compound	This product contains a maximum VOC content of 224 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time. Containers can burst violently or explode when heated, due to excessive pressure build-up.

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Mirror Image

Acute toxicity - oral

Notes (oral LD_{50})	Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD_{50})	Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC_{50})	Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data	Repeated exposure may cause skin dryness or cracking.
Extreme pH	Moderate pH (> 2 and < 11.5).

Serious eye damage/irritation

Serious eye damage/irritation	Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation	Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation	Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro	Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity	Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure	STOT SE 3 - H336 May cause drowsiness or dizziness.
Target organs	Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard	Based on available data the classification criteria are not met.

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause temporary eye irritation.

Mirror Image

Acute and chronic health hazards	This product has low toxicity. Only large quantities are likely to have adverse effects on human health.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target organs	Central nervous system
Medical symptoms	No specific symptoms noted, but this chemical may still have adverse health impact, either in general or on certain individuals. Prolonged or repeated exposure may cause the following adverse effects: Dry skin.

Toxicological information on ingredients.

Naphtha (petroleum), hydrotreated heavy

Acute toxicity - oral

Acute toxicity oral (LD_{50} mg/kg)	5,000.0
Species	Rat

Acute toxicity - dermal

Acute toxicity dermal (LD_{50} mg/kg)	5,000.0
Species	Rabbit

Dicocodimethylammonium chloride

Other health effects	There is no evidence that the product can cause cancer.

SECTION 12: Ecological information

Ecotoxicity	The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. Dangerous for the environment if discharged into watercourses.

Ecological information on ingredients.

Naphtha (petroleum), hydrotreated heavy

Ecotoxicity	The product is not expected to be toxic to aquatic organisms.

2,2'-(Octadec-9-enylimino)bisethanol

Ecotoxicity	The product contains a substance which is very toxic to aquatic organisms.

12.1. Toxicity

Toxicity	Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

Acute aquatic toxicity

Acute toxicity - fish	Not determined.
Acute toxicity - aquatic invertebrates	Not determined.
Acute toxicity - aquatic plants	Not determined.
Acute toxicity - microorganisms	Not determined.

Mirror Image

Acute toxicity - terrestrial Not determined.

Ecological information on ingredients.

2,2'-(Octadec-9-enylimino)bisethanol

Acute aquatic toxicity

LE(C)$_{50}$	0.01 < L(E)C50 ≤ 0.1
M factor (Acute)	10
Acute toxicity - fish	LC_{50}, 96 hours: 0.39 mg/l, Fish
Acute toxicity - aquatic invertebrates	EC_{50}, 48 hours: 0.1 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC_{50}, 72 hours: 0.01-0.1 mg/l, Algae

Chronic aquatic toxicity

M factor (Chronic)	1

Dicocodimethylammonium chloride

Acute aquatic toxicity

LE(C)$_{50}$	0.1 < L(E)C50 ≤ 1
M factor (Acute)	1
Acute toxicity - fish	LC_{50}, 96 hours: 0.195 mg/l, Fish
Acute toxicity - aquatic invertebrates	EC_{50}, 48 hours: 0.01-0.1 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

Naphtha (petroleum), hydrotreated heavy

Persistence and degradability	Volatile substances are degraded in the atmosphere within a few days.

2,2'-(Octadec-9-enylimino)bisethanol

Persistence and degradability	The product is readily biodegradable.

Dicocodimethylammonium chloride

Persistence and degradability	The product is biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

Mirror Image

Naphtha (petroleum), hydrotreated heavy

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

2,2'-(Octadec-9-enylimino)bisethanol

Bioaccumulative potential No data available on bioaccumulation.

Dicocodimethylammonium chloride

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility The product is insoluble in water. The product contains volatile substances which may spread in the atmosphere.

Ecological information on ingredients.

Naphtha (petroleum), hydrotreated heavy

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Dicocodimethylammonium chloride

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

Naphtha (petroleum), hydrotreated heavy

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current UK criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible.

Mirror Image

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

Transport labels
No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).
The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
EH40/2005 Workplace exposure limits.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems. Only trained personnel should use this material.

Classification procedures according to SI 2019 No. 720 STOT SE 3 - H336: : Calculation method. Aquatic Chronic 3 - H412: : Calculation method.

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this material.

Mirror Image

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain. www.autosmartinternational.com rbutler@autosmart.co.uk Tel +44 (0)1543 481616
Revision date	20/09/2022
Revision	17
Supersedes date	11/05/2021
SDS number	10109
SDS status	Approved.
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.