Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.08.2022 Part No: WA1211 - Textured Black Paint Revision: 16.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier** For Industrial, professional and consumer only

· **Trade name: Fleet Polyurethane**
· **1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating
· **Application of the substance / the mixture**
Surface Coating
Surface Coating

· **1.3 Details of the supplier of the safety data sheet**
· **Supplier:**
HMG PAINTS LIMITED
Riverside Works,
Collyhurst Road,
Collyhurst,
Manchester,
M40 7RU
UNITED KINGDOM
TEL: +44 (0)161 205 7631
EMAIL: sales@hmgpaint.com

· **Further information obtainable from:** sales@hmgpaint.com
· **1.4 Emergency telephone number:** +44 (0)161 205 7631 (business hours)

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**
· **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3	H226 Flammable liquid and vapour.
STOT SE 3	H336 May cause drowsiness or dizziness.
STOT RE 1	H372 Causes damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

· **2.2 Label elements**
· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**
Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics,
<2% aromatics
Hydrocarbons, C9-12, n-alkanes, isoalkanes,cyclics, aromatics (2-25%)
· **Hazard statements**
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.08.2022 *Revision: 16.03.2022*

Trade name: Fleet Polyurethane

(Contd. of page 1)

· **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**
· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	>10-≤25%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33-xxxx	Hydrocarbons, C9-12, n-alkanes, isoalkanes,cyclics, aromatics (2-25%) Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	>10-≤25%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light aromatic Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	>1-≤2.5%
CAS: 77-99-6 EINECS: 201-074-9 Reg.nr.: 01-2119486799-10	1,1,1-Trimethylolpropane Repr. 2, H361fd	≤1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **General information:** Immediately remove any clothing soiled by the product.
· **After inhalation:** Supply fresh air; consult doctor in case of complaints.
· **After skin contact:**
Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.
Immediately rinse with water.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:**
Do not induce vomiting; call for medical help immediately and show safety datasheet or label.
· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.08.2022 *Revision: 16.03.2022*

Trade name: Fleet Polyurethane

(Contd. of page 2)

SECTION 5: Firefighting measures

· ***5.1 Extinguishing media***
· ***Suitable extinguishing agents:***
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· ***For safety reasons unsuitable extinguishing agents:*** *Water with full jet*
· ***5.2 Special hazards arising from the substance or mixture***
During heating or in case of fire poisonous gases are produced.
· ***5.3 Advice for firefighters***
· ***Protective equipment:*** *Mount respiratory protective device.*

SECTION 6: Accidental release measures

· ***6.1 Personal precautions, protective equipment and emergency procedures***
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
· ***6.2 Environmental precautions:***
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
· ***6.3 Methods and material for containment and cleaning up:***
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
· ***6.4 Reference to other sections***
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· ***7.1 Precautions for safe handling***
Keep receptacles tightly sealed.
Ensure good ventilation/extraction at the workplace.
Prevent formation of aerosols.
Hygiene measures:
Wash hands before breaks and at the end of workday.
· ***Information about fire - and explosion protection:***
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

· ***7.2 Conditions for safe storage, including any incompatibilities***
· ***Storage:***
· ***Requirements to be met by storerooms and receptacles:***
Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washed out well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside.
· ***Information about storage in one common storage facility:*** *Not required.*
· ***Further information about storage conditions:***
Keep receptacle tightly sealed and in a well-ventilated place.
Keep away from heat.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.08.2022 *Revision: 16.03.2022*

Trade name: Fleet Polyurethane

(Contd. of page 3)

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**
· **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**	
Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
OEL	Short-term value: 1200 mg/m³
Solvent naphtha (petroleum), light aromatic	
OEL	Long-term value: 100 mg/m³

· **DNELs**		
Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	DNEL	125 mg/day (Con)
Dermal	DNEL	125 mg/day (Con)
		208 mg/day (Ind)
Inhalative	DNEL	185 mg/m³ (Con)
		871 mg/m³ (Ind)
Hydrocarbons, C9-12, n-alkanes, isoalkanes,cyclics, aromatics (2-25%)		
Oral	DNEL	26 mg/day (Con)
Dermal	DNEL	26 mg/day (Con)
		44 mg/day (Ind)
Inhalative	DNEL	71 mg/m³ (Con)
		330 mg/m³ (Ind)
Solvent naphtha (petroleum), light aromatic		
Oral	DNEL	11 mg/day (Con)
Dermal	DNEL	11 mg/day (Con)
		25 mg/day (Ind)
Inhalative	DNEL	32 mg/m³ (Con)
		150 mg/m³ (Ind)
77-99-6 1,1,1-Trimethylolpropane		
Oral	DNEL	0.34 mg/day (Con)
Dermal	DNEL	0.34 mg/day (Con)
		0.94 mg/day (Ind)
Inhalative	DNEL	0.58 mg/m³ (Con)
		3.3 mg/m³ (Ind)

· **PNECs**
CAS No. 1330-20-7 Xylene mixed isomers
- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l
- STP; 6.58 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marinewater); 12.46 mg/kg
- Soil; 2.31 mg/kg

· **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.08.2022 *Revision: 16.03.2022*

Trade name: Fleet Polyurethane

(Contd. of page 4)

· **8.2 Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
· **Respiratory protection:** When spraying the product, use a respiratory protective device.
· **Protection of hands:**
When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective gloves

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Liquid
Colour:	According to product specification
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined.
· **pH-value:**	Not determined.
· **Change in condition**	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	135 °C
· **Flash point:**	31 °C
· **Flammability (solid, gas):**	Not applicable.
· **Ignition temperature:**	>200 °C
· **Decomposition temperature:**	Not determined.
· **Auto-ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· **Explosion limits:**	
Lower:	0.6 Vol %
Upper:	7 Vol %
· **Vapour pressure at 20 °C:**	6.6 hPa
· **Density at 20 °C:**	1.077 g/cm³
· **Relative density**	Not determined.
· **Vapour density**	Not determined.
· **Evaporation rate**	Not determined.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.08.2022 *Revision: 16.03.2022*

Trade name: Fleet Polyurethane

(Contd. of page 5)

· **Solubility in / Miscibility with water:**	NOT MISCIBLE
· **Partition coefficient: n-octanol/water:**	Not determined.
· **Viscosity:**	
Dynamic at 20 °C:	250 mPas
Kinematic:	Not determined.
· **Solvent content:**	
Organic solvents:	40.0 %
Solids content:	59.6 %
· **9.2 Other information**	No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** No dangerous reactions known.
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:**
No dangerous decomposition products when stored and handled correctly

SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**		
Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (Rat)
Hydrocarbons, C9-12, n-alkanes, isoalkanes,cyclics, aromatics (2-25%)		
Oral	LD50	>15,000 mg/kg (Rat)
Dermal	LD50	>3,400 mg/kg (Rab)
Inhalative	LC50/4 h	13.1 mg/l (Rat)
Solvent naphtha (petroleum), light aromatic		
Oral	LD50	3,492 mg/kg (rat)
Dermal	LD50	3,160 mg/kg (Rab)
Inhalative	LC50/4 h	>6.193 mg/l (rat)
77-99-6 1,1,1-Trimethylolpropane		
Oral	LD50	14,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rab)
Inhalative	LC50/4 h	>0.29 mg/l (rat)

· **Primary irritant effect:**
· **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
· **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.08.2022 *Revision: 16.03.2022*

Trade name: Fleet Polyurethane

(Contd. of page 6)

· ***Additional toxicological information:***
· ***CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)***
· ***Germ cell mutagenicity*** *Based on available data, the classification criteria are not met.*
· ***Carcinogenicity*** *Based on available data, the classification criteria are not met.*
· ***Reproductive toxicity*** *Based on available data, the classification criteria are not met.*
· ***STOT-single exposure***
May cause drowsiness or dizziness.
· ***STOT-repeated exposure***
Causes damage to organs through prolonged or repeated exposure.
· ***Aspiration hazard*** *Based on available data, the classification criteria are not met.*

SECTION 12: Ecological information

· ***12.1 Toxicity***
· ***Aquatic toxicity:***
Acute Fish toxicity
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
LC50 9.22 mg/l
Species: Oncorhynchus mykiss (rainbow trout)
Exposure duration: 96 h

Acute toxicity for daphnia
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
EC50 6.14 mg/l
Species: Daphnia magna (Water flea)
Exposure duration: 48 h

Acute toxicity for algae
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
ErC50 2.9 mg/l
Species: Pseudokirchneriella subcapitata (green algae)
Exposure duration: 72 h

Acute bacterial toxicity
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
EC50 1 - 10 mg/l

Ecotoxicology Assessment
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
Chronic aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Data based on the safety data sheet (SDS) by the supplier.
· ***12.2 Persistence and degradability*** *No further relevant information available.*
· ***12.3 Bioaccumulative potential*** *No further relevant information available.*
· ***12.4 Mobility in soil*** *No further relevant information available.*
· ***Ecotoxical effects:***
· ***Remark:*** *Harmful to fish*
· ***Additional ecological information:***
· ***General notes:***
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
· ***12.5 Results of PBT and vPvB assessment***
· ***PBT:*** *Not applicable.*
· ***vPvB:*** *Not applicable.*

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.08.2022 Revision: 16.03.2022

Trade name: Fleet Polyurethane

(Contd. of page 7)

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**	
· **ADR, IMDG, IATA**	UN1263
· **14.2 UN proper shipping name**	
· **ADR**	1263 PAINT RELATED MATERIAL
· **IMDG, IATA**	PAINT RELATED MATERIAL
· **14.3 Transport hazard class(es)**	
· **ADR, IMDG, IATA**	



· **Class**	3 Flammable liquids.
· **Label**	3
· **14.4 Packing group**	
· **ADR, IMDG, IATA**	III
· **14.5 Environmental hazards:**	
· **Marine pollutant:**	no No
· **14.6 Special precautions for user**	Warning: Flammable liquids.
· **Hazard identification number (Kemler code):**	30
· **EMS Number:**	F-E,S-E
· **Stowage Category**	A
· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**	Not applicable.
· **Transport/Additional information:**	
· **ADR**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **Transport category**	3
· **Tunnel restriction code**	D/E
· **IMDG**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.08.2022 *Revision: 16.03.2022*

Trade name: Fleet Polyurethane

(Contd. of page 8)

· **UN "Model Regulation":** UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category** P5c FLAMMABLE LIQUIDS
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	40.0

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Full text of H-Statements referred to under sections 2 and 3:**
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Product safety department: LABORATORY
· **Contact:** Health & Safety Officer
· **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3