TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 01485R-FLU

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	RENOLIT CL X2	Pseudonym	Lubricating Grease
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance Use: Frequent, daily, short periods at a time	Location of process being carried out	Customers site, Toyota Workshops

Identify the persons at risk	Team members ✓	Sub-contractors ☐	Customer Team member ☐	Public ☐

Labelling Elements

 ☐ Explosive

 ☐ Health Hazard

 ☐ Serious Health Hazard

 ☐ Oxidising

 ☐ Corrosive

 ☐ Acute

 ☐ Flammable

 ☐ Environmental

 ☐ Gas

The product has not been classified as hazardous, but needs to be labelled according to regulation GB-CLP.

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	☐	☐	☐	☐	☐	✓	☐

Additional Information: Paste

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
☐	✓	✓	☐	☐

Additional Information: May cause skin and eye irritation. May cause an allergic reaction.

Control Measures

Use in adequately ventilated area.
Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned. Instantly remove any clothing soiled by the product.
Take usual precautions when handling mineral oil products or chemical products.
Use personal protective equipment as required – See SWP-32. Avoid contact with skin and eyes. If risk of splashing, wear safety goggles.
Safety glasses (EN 166) recommended during refilling.
Avoid long-term and repeated skin contact. Use skin protection cream for preventive skin protection.
Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.
This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes ☐	No ✓

Provide details:

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: 01485R-FLU

Personal Protective Equipment Required							
 ☐	 ☐	 ☐	 √	 ✓	 ✓	 ✓	 ☐
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
Additional Information:	Disposable gloves						

First Aid Measures	
Inhalation:	Supply fresh air; consult doctor in case of symptoms.
Skin Contact:	Wash with soap and water.
Eye Contact:	Promptly wash eyes with plenty of water while lifting the eye lids.
Ingestion:	Rinse mouth thoroughly.

Storage
Keep stock levels to as minimum as possible. Store in the original clearly identified containers. Store in a cool well ventilated area. Storage Class: 11, Combustible solids
Spillage
Clean up any spills or excess product immediately to prevent slips – See SWP-19. Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water. Scrape up spillage or absorb with absorbing material. Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.
Disposal of Substance & Contaminated Containers

☐	☐	✓	☐	☐
Hazardous Waste	General Waste	Return to Depot	Return to Supplier	Other

Additional Information: All waste to be disposed of at a suitable recycling facility.

Is exposure adequately controlled	Yes ✓	No ☐

Risk Rating Following Control Measures		
High ☐	Medium ☐	Low ✓

Assessed by:	Elaine Greaves	Date:	December 2025	Review Date:	June 2027