TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 02037R-JAM

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	FLT Chain Lubricant	Pseudonym	Chain Spray
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance, frequent, daily, short periods at a time, seconds/minute	Location of process being carried out	Customer Site, Toyota Workshops

Identify the persons at risk	Team members √	Sub-contractors ☐	Customer Team member ☐	Public ☐

Labelling Elements


☐ Explosive


☐ Health Hazard


☐ Serious Health Hazard


☐ Oxidising


☐ Corrosive


☐ Acute


√ Flammable


☐ Environmental


☐ Gas

Signal Word: DANGER

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	√	√	☐	☐	√	☐	☐

Additional Information: Aerosol

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
√	√	√	☐	☐

Additional Information: Irritant

Control Measures

Keep quantities to as minimal as is practicable.
Extremely flammable aerosol. Pressurised container: may burst if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Keep out of reach of children.
Avoid breathing vapour/ spray. Use only outdoors or in a well-ventilated area. Avoid contact with eyes.
Use correct PPE – see SWP-32 and below
Good personal hygiene procedures should be implemented. Wash contaminated skin thoroughly after handling. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash after use and before eating, smoking and using the toilet.
This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes ☐	No √

Provide details:

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: 02037R-JAM

Personal Protective Equipment Required							
			 √	 √	 √	 √	
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
			EN166.	EN374			

Additional Information:

First Aid Measures	
Inhalation:	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Skin Contact:	Remove contamination with soap and water or recognised skin cleansing agent.
Eye Contact:	Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical attention if any discomfort continues.
Ingestion:	Rinse mouth thoroughly with water. If in doubt, get medical attention promptly. Due to the small packaging, the risk of ingestion is minimal. Do not induce vomiting unless under the direction of medical personnel.

Storage

Keep out of reach of children. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep away from oxidising materials, heat and flames. Store in a cool and well-ventilated place. Keep containers upright. Protect containers from damage.

Spillage

See SWP-19. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Ensure there is adequate ventilation. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely.

Disposal of Substance & Contaminated Containers

Hazardous Waste	General Waste	Depot	Return to Supplier	Other
		√		

Additional Information: Dispose of contents/ container in accordance with local regulations. Do not pierce or burn, even after use

Is exposure adequately controlled	Yes √	No

Risk Rating Following Control Measures

High	Medium	Low √

Assessed by:	Elaine Greaves	Date:	Feb 2026	Review Date:	August 2027