TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 030926PRO

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	QDP 1K Topcoat RM	Pseudonym	QDP 1K Topcoat RM
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	Depot Maintenance. Refurbish Depot trucks and barriers. No more than annually, limited use	Location of process being carried out	TMHUK Depots

Identify the persons at risk	Team members √	Sub-contractors	Customer Team member	Public

Labelling Elements

 Explosive ☐

 √ Health Hazard

 √ Serious Health Hazard

 Oxidising ☐

 Corrosive ☐

 Acute ☐

 √ Flammable

 √ Environmental

 Gas ☐

Signal Word: Danger

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	√	☐	☐	√	√	☐	☐

Additional Information:

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
√	√	√	√	☐

Additional Information: Flammable liquid and vapour. May cause drowsiness or dizziness.

Control Measures

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking. Do not breathe vapour.
Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.
Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wear appropriate personal protective equipment as listed below
Always keep in containers made from the same material as the original one.
Do not allow to enter drains or watercourses.
Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Use where there is adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL (see MSDS), suitable respiratory protection must be

worn.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes ☐	No ☑

Provide details:

Personal Protective Equipment Required

Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
☐	☐	☐	☑	☑	☑	☑	☑

Additional Information: When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator.
Ensure that eyewash stations and safety showers are close to the workstation location.

First Aid Measures

Inhalation:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin Contact:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Eye Contact:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Ingestion:	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Storage

Keep away from: oxidising agents, strong alkalis, strong acids. Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.
Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Spillage

See SWP-19. Do not allow to enter drains or watercourses. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with a detergent.
Avoid using solvents.

Disposal of Substance & Contaminated Containers

Hazardous Waste	General Waste	Depot	Return to Supplier	Other
☐	☐	☑	☐	☐

Additional Information:

COSHH Risk Assessment:

Part Number: 030926PRO

Is exposure adequately controlled		Yes √		No	
Risk Rating Following Control Measures					
High		Medium		Low √	
Assessed by:	Elaine Greaves	Date:	December 2025	Review Date:	June 2027