TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 130009PRO

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Low Temp. Chain Lubricant 400ml Aerosols	Pseudonym	Chain Lubricant
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance Use: often used on a weekly basis for a few minutes at a time.	Location of process being carried out	Customers Site & Toyota Workshops

Identify the persons at risk	Team members ✓	Sub-contractors ☐	Customer Team member ☐	Public ☐

Labelling Elements


☐ Explosive


☐ Health Hazard


☐ Serious Health Hazard


☐ Oxidising


☐ Corrosive


☐ Acute


✓ Flammable


☐ Environmental


☐ Gas

Signal Word: DANGER

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	✓	✓	☐	☐	☐	☐	☐

Additional Information: ✓

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
✓	✓	✓	☐	☐

Additional Information: Irritant, Vapours in high concentrations are narcotic.

Control Measures

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source.
Avoid breathing vapour/ spray, Use only outdoors or in a well-ventilated area.

Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke when using this product.

Wear appropriate PPE – see below and SWP-32

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes ☐	No ✓
Provide details:		

Personal Protective Equipment Required

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: 130009PRO

 ☐	 ☐	 ☐	 ✓	 ✓	 ✓	 ✓	 ☐
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other

Additional Information: If ventilation is inadequate, suitable respiratory protection must be worn.

First Aid Measures	
Inhalation:	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.
Skin Contact:	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye Contact:	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.
Ingestion:	Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.

Storage
Keep out of reach of children. Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame. Do not expose to temperatures exceeding 50°C/122°F.
Spillage
Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas. Avoid discharge into drains. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. See SWP-19
Disposal of Substance & Contaminated Containers

☐	☐	✓	☐	☐
Hazardous Waste	General Waste	Return to Depot	Return to Supplier	Other

Additional Information: Dispose of waste product or used containers in accordance with local regulations

Is exposure adequately controlled	Yes ✓	No ☐
Risk Rating Following Control Measures		
High ☐	Medium ☐	Low ✓

Assessed by:	Elaine Greaves	Date:	February 2023	Review Date:	August 2025