TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 130019PRO

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Grey Spray Paint 400ml Aerosol. Prod No:938	Pseudonym	Grey Spray Paint
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT maintenance USE: infrequent, less than daily, seconds/ minute or so at a time. TMHUK Paint shop USE: Frequent, Daily.	Location of process being carried out	Customer Site, Toyota workshops

Identify the persons at risk	Team members	✓	Sub-contractors		Customer Team member	✓	Public	

Labelling Elements

 ☐ Explosive

 ✓ Health Hazard

 ☐ Serious Health Hazard

 ☐ Oxidising

 ☐ Corrosive

 ☐ Acute

 ✓ Flammable

 ☐ Environmental

 ☐ Gas

Signal Word: DANGER

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	✓	✓	☐	☐	✓	☐	☐

Additional Information: Solvent Aerosol

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
✓	✓	✓	☐	☐

Additional Information: May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.

Control Measures

Read and follow manufacturer's recommendations. Use personal protection equipment as listed below.
Keep out of reach of children.
Keep away from heat, sparks and open flame. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.
The anticipated use of this product is for touching up small areas of damaged paintwork. If used for painting large areas Respiritory Protective Equipment is required. Do not breathe vapour/ spray. Use suitable respiratory protection if ventilation is inadequate – See SWP-32
Maintain good hygiene standards at all times - Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke
Maintain quantities to as minimal as practicable.
This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: 130019PRO

Is health surveilance or monitoring required?	Yes ☐	No ☑

Provide details: Health Surveilance required if recommended daily exposure level exceeded, to be monitored locally.

Personal Protective Equipment Required


Dust Mask ☐


Visor ☐


Respirator ☐


Goggles ☑


Gloves ☑


Overalls ☑


Footwear ☑


Other ☐

Additional Information: If used for painting large areas Respiritory Protective Equipment is required

First Aid Measures

Inhalation:	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Skin Contact:	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Eye Contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Ingestion:	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.

Storage

Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals.

Spillage

Due to container size any spills are foreseen as small. Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas. Avoid discharge into drains. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Clean up as per SWP – 19.

Disposal of Substance & Contaminated Containers

Hazardous Waste	General Waste	Return to Depot	Return to Supplier	Other
☑	☐	☑	☐	☐

Additional Information: Dispose of waste product or used containers in accordance with local regulations. Make sure containers are empty before discarding (explosion risk). Do not puncture or incinerate even when empty.

Is exposure adequately controlled	Yes ☑	No ☐

Risk Rating Following Control Measures

High	Medium	Low
☐	☐	☑

COSHH Risk Assessment:

Part Number: 130019PRO

Assessed by:	Elaine Greaves	Date:	January 2026	Review Date:	July 2027