TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 130022PRO

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Black Spray Paint 400ml Aerosol	Pseudonym	Black Spray Paint
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT maintenance USE: infrequent, less than daily, seconds/ minute or so at a time. TMHUK Paint shop USE: Frequent, Daily.	Location of process being carried out	Customer Site, Toyota workshops

Identify the persons at risk	Team members	✓	Sub-contractors		Customer Team member	✓	Public	

Labelling Elements


☐ Explosive


☑ Health Hazard


☑ Serious Health Hazard


☐ Oxidising


☐ Corrosive


☐ Acute


☑ Flammable


☐ Environmental


☐ Gas

Signal Word: DANGER

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	✓	✓	☐	☐	✓	☐	☐

Additional Information: Solvent Aerosol

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
✓	✓	✓	☐	☐

Additional Information: May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Control Measures

Read and follow manufacturer's recommendations. Maintain quantities to as minimal as practicable.
Keep out of reach of children.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
The anticipated use of this product is for touching up small areas of damaged paintwork.
Use only outdoors or in a well-ventilated area
If used for painting large areas Respiritory Protective Equipment is required. Do not breathe vapour/ spray.
Use personal protection equipment as listed below. See SWP-32
Maintain good hygiene standards at all times - Do not eat, drink or smoke when using this product.
Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.
This product poses no significant risk if used as intended in the amount anticipated, and

manufactures instructions are followed.	
Is health surveilance or monitoring required?	Yes ☐ No ☑
Provide details: Health Surveilance required if recommended daily exposure level exceeded, to be monitored locally.	

Personal Protective Equipment Required

 ☐ Dust Mask
 ☐ Visor
 ☐ Respirator
 ☑ Goggles
 ☑ Gloves
 ☑ Overalls
 ☑ Footwear
 ☐ Other

Additional Information: If used for painting large areas Respiritory Protective Equipment is required

First Aid Measures

Inhalation:	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur.
Skin Contact:	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Eye Contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Ingestion:	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.

Storage

Keep stocked levels to a minimum.
Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Do not expose to temperatures exceeding 50 °C/122 °F. Keep in properly labelled containers. Do not store near combustible materials.
Store in accordance with local regulations.

Spillage

Due to container size any spills are foreseen as small. Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas. Avoid discharge into drains. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Clean up as per SWP – 19.

Disposal of Substance & Contaminated Containers

☑ Hazardous Waste ☐ General Waste ☑ Return to Depot ☐ Return to Supplier ☐ Other

Additional Information: Dispose of waste product or used containers in accordance with local regulations. Make sure containers are empty before discarding (explosion risk). Do not puncture or incinerate even when empty.

Is exposure adequately controlled	Yes ☑ No ☐

COSHH Risk Assessment:

Part Number: 130022PRO

Risk Rating Following Control Measures					
High ☐		Medium ☐		Low ☑	
Assessed by:	Elaine Greaves	Date:	January 2026	Review Date:	July 2027