TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 130031PRO

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Mast Lubricant 400ml Aerosol	Pseudonym	Mast Lubricant
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance Use: Frequent, daily for seconds at a time.	Location of process being carried out	Customers Site & Toyota Workshops

Identify the persons at risk	Team members ✓	Sub-contractors ☐	Customer Team member ☐	Public ☐

Labelling Elements

 ☐ Explosive

 ☐ Health Hazard

 ☐ Serious Health Hazard

 ☐ Oxidising

 ☐ Corrosive

 ☐ Acute

 ✓ Flammable

 ☐ Environmental

 ☐ Gas

Extremely flammable aerosol.

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	✓	✓	☐	☐	☐	☐	☐

Additional Information: Aerosol.

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
✓	✓	✓	☐	☐

Additional Information: Irritant, Vapours in high concentrations are narcotic

Control Measures

Extremely flammable aerosol. Pressurised container: may burst if heated. Do not pierce or burn, even after use. Harmful to aquatic life with long lasting effects. Avoid release to the environment.

Avoid breathing vapour/ spray. Use only outdoors or in a well-ventilated area.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations.
Wash promptly with soap and water if skin becomes contaminated.
Do not eat, drink or smoke when using this product.

Wear appropriate PPE. See below and SWP-32.

Keep stock levels to as minimum as is practicable

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: 130031PRO

Is health surveilance or monitoring required?	Yes ☐	No ☑

Provide details:

Personal Protective Equipment Required


Dust Mask ☐


Visor ☐


Respirator ☐


Goggles ☑


Gloves ☑


Overalls ☑


Footwear ☑


Other ☐

Additional Information: If ventilation is inadequate, suitable respiratory protection must be worn.

First Aid Measures

Inhalation:	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.
Skin Contact:	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye Contact:	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.
Ingestion:	Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.

Storage

Keep out of reach of children. Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

Spillage

Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas. Avoid discharge into drains. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. See SWP-19

Disposal of Substance & Contaminated Containers

Hazardous Waste ☐ General Waste ☐ Return to Depot ☑ Return to Supplier ☐ Other ☐

Additional Information: Dispose of contents/ container in accordance with national regulations

Is exposure adequately controlled	Yes ☑	No ☐

Risk Rating Following Control Measures

High ☐ Medium ☐ Low ☑

Assessed by:	Elaine Greaves	Date:	April 2026	Review Date:	October 2027