TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 130054PRO

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Ultra Life Product number 0250/0580	Pseudonym	Ultra Life Grease
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance. Lubricating grease. Use: Frequent, daily, short periods at a time	Location of process being carried out	Customers site & Toyota Workshops

Identify the persons at risk	Team members	Sub-contractors	Customer Team member	Public
	✓			

Labelling Elements

 ☐ Explosive

 ☐ Health Hazard

 ☐ Serious Health Hazard

 ☐ Oxidising

 ☐ Corrosive

 ☐ Acute

 ☐ Flammable

 ☐ Environmental

 ☐ Gas

Not Classified

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	☐	☐	☐	☐	☐	✓	☐

Additional Information: Semi Solid, Smooth Red Grease

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
☐	✓	✓	√	☐

Additional Information: Slight Irritant

Control Measures

Wear protective clothing, see SWP-32. Keep away from food, drink and animal feeding stuffs.
Keep container tightly sealed when not in use. Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.
Wash hands thoroughly after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.
This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes	No
	☐	✓

Provide details:

Personal Protective Equipment Required

Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
☐	☐	✓	✓	✓	✓	✓	✓

COSHH Risk Assessment:

Part Number: 130054PRO

Additional Information: Eye protection should only be necessary where liquid could be splashhed or sprayed. If the ventilation is suitable, it is not essential to wear respiratory equipment. Use barrier cream. Boots, gloves and goggles.	
First Aid Measures	
Inhalation:	If throat irritation or coughing persists, move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if any discomfort continues.
Skin Contact:	Wash skin thoroughly with mild soap and water. Take off contaminated clothing and wash it before reuse. Get medical attention if any discomfort continues.
Eye Contact:	Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical attention if any discomfort continues.
Ingestion:	Rinse mouth out with water. Do not induce vomiting. Unless directed to do so by medical personnel. Get medical attention if any discomfort continues.

Storage
Keep stock levels to as minimum as possible. Store in the original clearly identified containers. Store in a cool well ventilated area.
Spillage
Clean up spilled product immediately will spill kits provided, see SWP-19 Spillage. For a larger spillage contain the spillage by bunding. Particular danger of slipping on leaked/spilled product. Dispose of contents/container in accordance with national regulations. Avoid discharge into drains or watercourses or onto the ground. Reuse or recycle products wherever possible. Collect spillage with a shovel and broom, or similar and reuse, if possible. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage.
Disposal of Substance & Contaminated Containers
☐ Hazardous Waste ☐ General Waste ☑ Return to Depot ☐ Return to Supplier ☐ Other Additional Information:

Is exposure adequately controlled	Yes ☑		No ☐		
Risk Rating Following Control Measures					
High ☐	Medium ☐		Low ☑		
Assessed by:	Elaine Greaves	Date:	January 2026	Review Date:	July 2027