TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 243531

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	POLYLUB GLY 801 Article-No. : 020199	Pseudonym	Grease
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance – Use: Daily, minutes at a time	Location of process being carried out	Customer Sites & TMHUK Workshops

Identify the persons at risk	Team members √	Sub-contractors	Customer Team member	Public

Labelling Elements


Explosive ☐


Health Hazard ☐


Serious Health Hazard ☐


Oxidising ☐


Corrosive ☐


Acute ☐


Flammable ☐


Environmental ☐


Gas ☐

Not Classified

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	☐	☐	☐	☐	☐	☐	√

Additional Information: Paste

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
☐	☐	☐	☐	☐

Additional Information: None listed on MSDS

Control Measures

Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Wear PPE as highlighted below
This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes ☐	No √

Provide details:

Personal Protective Equipment Required

Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
☐	☐	☐	√	√	√	√	☐
				EN 374			

Additional Information:

COSHH Risk Assessment:

Part Number: 243531

First Aid Measures	
Inhalation:	Remove person to fresh air. If signs/symptoms continue, get medical attention. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.
Skin Contact:	Remove contaminated clothing. If irritation develops, get medical attention. In case of contact, immediately flush skin with plenty of water.
Eye Contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes. If eye irritation persists, consult a specialist.
Ingestion:	Move the victim to fresh air. Do not induce vomiting without medical advice.

Storage
Store in original container. Keep container closed when not in use. Keep in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.
Spillage
See SWP-19. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained. Clean up promptly by sweeping or vacuum. Keep in suitable, closed containers for disposal.
Disposal of Substance & Contaminated Containers

☐	☐	√	☐	☐
Hazardous Waste	General Waste	Depot	Return to Supplier	Other

Additional Information:

Is exposure adequately controlled		Yes √		No ☐	
Risk Rating Following Control Measures					
High ☐		Medium ☐		Low √	
Assessed by:	Elaine Greaves	Date:	January 2026	Review Date:	July 2027