TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 263040-UAD

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Gerion Plus 75W90	Pseudonym	Gear oil EP 75W90
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance Infrequent, less than weekly, for short periods only	Location of process being carried out	Customers Site, Toyota Workshops

Identify the persons at risk	Team members [√]	Sub-contractors [ ]	Customer Team member [ ]	Public [ ]

Labelling Elements


[ ] Explosive


[ ] Health Hazard


[ ] Serious Health Hazard


[ ] Oxidising


[ ] Corrosive


[ ] Acute


[ ] Flammable


[√] Environmental


[ ] Gas

Harmful to aquatic life with long lasting effects. Avoid release to the environment Dispose of contents/container to a hazardous or special waste collection point

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
[ ]	[ ]	[ ]	[ ]	[ ]	[√]	[ ]	[ ]

Additional Information: Lubricant - Oily

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
[ ]	[√]	[√]	[ ]	[ ]

Additional Information: May cause slight irritation.

Control Measures

Use personal protective equipment as required. Not expected to present a significant hazard under anticipated conditions of normal use. Provide good ventilation in process area to prevent formation of vapour. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes [ ]	No [√]

Provide details:

Personal Protective Equipment Required

Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
[ ]	[ ]	[ ]	[√]	[√]	[√]	[√]	[ ]

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: 263040-UAD

Additional Information: Avoid the formation of mists in the atmosphere. If this material is handled at elevated temperature or under mist forming conditions, approved respiratory protection equipment should be used	
First Aid Measures	
Inhalation:	Remove person to fresh air and keep comfortable for breathing.
Skin Contact:	Wash skin with plenty of water.
Eye Contact:	Rinse eyes with water as a precaution.
Ingestion:	Call a POISON CENTER or doctor/physician if you feel unwell.

Storage
Store in original container. Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep in fireproof place.
Spillage
See SWP-19. May be dangerously slippery if spilled. Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible. Take up liquid spill into absorbent material.
Disposal of Substance & Contaminated Containers
☐ Hazardous Waste ☐ General Waste ☑ Return to Depot ☐ Return to Supplier ☐ Other Additional Information: Dispose of materials or solid residues at an authorized site.

Is exposure adequately controlled	Yes ☑		No ☐		
Risk Rating Following Control Measures					
High ☐	Medium ☐		Low ☑		
Assessed by:	Elaine Greaves	Date:	October 2026	Review Date:	April 2028