TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 326RAG

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	LOCTITE AA 326	Pseudonym	Loctite 326
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance. Acrylic Adhesive. Use: Less than weekly, minutes at a time	Location of process being carried out	Customer Sites / TMHUK Workshops

Identify the persons at risk	Team members	Sub-contractors	Customer Team member	Public
	√			

Labelling Elements


☐ Explosive


☑ Health Hazard


☐ Serious Health Hazard


☐ Oxidising


☐ Corrosive


☐ Acute


☐ Flammable


☐ Environmental


☐ Gas

Signal Word: WARNING

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	√	☐	☐	☐	√	☐	☐

Additional Information: Transparent Amber Liquid

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
√	√	√	☐	☐

Additional Information: Iritant and allergen.

Control Measures

Acrylate adhesive
Do not let product enter drains.
Use only in well-ventilated areas.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)
Avoid skin and eye contact.
Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Good industrial hygiene practices should be observed.
Wear PPE as listed below.
This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes	No
	☐	√

Provide details:

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: 326RAG

Personal Protective Equipment Required							
 ☐	 ☐	 ☐	 √	 √	 √	 √	 ☐
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
		Filter type: A	EN 166	EN 374	EN 14605		
Additional Information: If signs of wear and tear are noticed then the gloves should be replaced.							

First Aid Measures	
Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
Skin Contact:	Rinse with running water and soap. Obtain medical attention if irritation persists.
Eye Contact:	Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.
Ingestion:	Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Storage
Keep out of reach of children. Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.
Spillage
See SWP-19. For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Avoid skin and eye contact. Do not let product enter drains.
Disposal of Substance & Contaminated Containers

☐ Hazardous Waste	☐ General Waste	√ Depot	☐ Return to Supplier	☐ Other

Additional Information: After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.
Disposal must be made according to official regulations.

Is exposure adequately controlled	Yes √	No ☐

Risk Rating Following Control Measures		
High ☐	Medium ☐	Low √

Assessed by:	Elaine Greaves	Date:	March 2024	Review Date:	September 2026