TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 40707S-HAH

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Citrus Clean	Pseudonym	Degreaser
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance - Cleaning product for professional use. Use: Infrequent, less than daily for seconds at a time.	Location of process being carried out	Customer sites & Toyota workshops

Identify the persons at risk	Team members	Sub-contractors	Customer Team member	Public
	√			

Labelling Elements


Explosive ☐


Health Hazard ☐


Serious Health Hazard ☐


Oxidising ☐


Corrosive ☐


Acute ☐


Flammable ☐


Environmental √


Gas ☐

Not Classified

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	☐	☐	☐	☐	√	☐	√

Additional Information:

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
☐	√	√	√	☐

Additional Information: May produce an allergic reaction. Irritant

Control Measures

Ensure there is sufficient ventilation of the area.
Respiratory protection not required.
Wear Protective gloves, Safety goggles are not normally required. However their use is recommended where there is a risk of spray mist or splashing when using or handling product.
Wear appropriate clothing to prevent any possibility of skin contact.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes	No
	☐	√

Provide details:

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: 40707S-HAH

Personal Protective Equipment Required							
				 √	 √	 √	
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other

Additional Information:

First Aid Measures	
Inhalation:	No symptoms.
Skin Contact:	Wash immediately with plenty of soap and water.
Eye Contact:	Bathe the eye with running water for 15 minutes.
Ingestion:	Wash out mouth with water.

Storage
Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.
Spillage
See SWP-19. Turn leaking containers leakside up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.
Disposal of Substance & Contaminated Containers

	√			
Hazardous Waste	General Waste	Depot	Return to Supplier	Other

Additional Information:

Is exposure adequately controlled	Yes √	No	
Risk Rating Following Control Measures			
High		Medium		Low √

Assessed by:	Elaine Greaves	Date:	May 2026	Review Date:	November 2027