TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 55319FP71071

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Teroson Bond 60	Pseudonym	Teroson Bond 60
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	Maintenance of FLT. adhesive and sealant for direct glazing. Use: less than weekly, minutes at a time	Location of process being carried out	TMHUK Workshops and Customer Premises

Identify the persons at risk	Team members √	Sub-contractors	Customer Team member	Public

Labelling Elements

 Explosive ☐

 Health Hazard ☐

 Serious Health Hazard √

 Oxidising ☐

 ☐

 Acute ☐

 Flammable ☐

 Environmental ☐

 Gas ☐

Corrosive

Signal Word: DANGER

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	☐	☐	☐	☐	☐	√	☐

Additional Information: Paste

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
√	√	☐	☐	☐

Additional Information: SKIN: Rash, Urticaria.
RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

Control Measures

Wear PPE as described below.
Hygiene measures: Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.
Use only in well ventilated areas.
Do not empty into drains, soil or bodies of water.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes ☐	No √

Provide details:

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: 55319FP71071

Personal Protective Equipment Required							
 √			 √	 √	 √		
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other

Additional Information: Personal protective equipment should conform to the relevant EN standard.

First Aid Measures	
Inhalation:	Fresh air, oxygen supply, warmth; seek specialist medical attention. Delayed effects possible after inhalation.
Skin Contact:	IF ON SKIN: Wash with plenty of soap and water. In case of adverse health effects seek medical advice.
Eye Contact:	Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.
Ingestion:	Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Storage
Ensure good ventilation/extraction. Temperatures between + 5 °C and + 35 °C
Spillage
See SWP-19. Wear protective equipment. Avoid contact with skin and eyes. Keep unprotected persons away. Do not empty into drains / surface water / ground water. Where possible remove mechanically
Disposal of Substance & Contaminated Containers

☐	☐	√	☐	☐
Hazardous Waste	General Waste	Depot	Return to Supplier	Other

Additional Information:

Is exposure adequately controlled	Yes √	No ☐			
Risk Rating Following Control Measures					
High ☐	Medium ☐	Low √			
Assessed by:	Elaine Greaves	Date:	June 2023	Review Date:	December 2025