TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: 7063RAG

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Loctite 7063 Aerosol	Pseudonym	Loctite 7063 Aerosol
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance. Solvent based cleaner. Use: less than weekly, minutes at a time	Location of process being carried out	Customer Sites/ TMHUK Workshops

Identify the persons at risk	Team members	Sub-contractors	Customer Team member	Public
	√			

Labelling Elements


Explosive ☐


√ Health Hazard


Serious Health Hazard ☐


Oxidising ☐


Corrosive ☐


Acute ☐


√ Flammable


√ Environmental


Gas ☐

Signal Word: Danger

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	√	√	☐	☐	√	☐	☐

Additional Information: Aerosol

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
√	√	√	☐	☐

Additional Information: SKIN: Redness, inflammation. Prolonged or repeated contact may cause eye irritation. Vapors may cause drowsiness and dizziness.

Control Measures

Flammable aerosol. Avoid Heat, flames, sparks and other sources of ignition.
Keep away from sources of ignition - no smoking.
Use only in well-ventilated areas. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)
Avoid skin and eye contact.
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Good industrial hygiene practices should be observed.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes	No
	☐	√

Provide details:

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: 7063RAG

Personal Protective Equipment Required							
			 √	 √	 √	 √	
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
		EN 14387	EN166.	EN 374	EN 14605		

Additional Information: If signs of wear and tear are noticed then the gloves should be replaced.

First Aid Measures	
Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
Skin Contact:	Rinse with running water and soap. Obtain medical attention if irritation persists.
Eye Contact:	Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.
Ingestion:	Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Storage

Store in a cool, dry place. Do not store near sources of heat or ignition, or reactive materials.
Refer to Technical Data Sheet

Spillage

See SWP-19. Remove sources of ignition. Ensure adequate ventilation. Avoid contact with skin and eyes. Wear protective equipment. Do not let product enter drains. Wipe up using absorbent material. Store in a partly filled, closed container until disposal.

Disposal of Substance & Contaminated Containers

Hazardous Waste	General Waste	Depot	Return to Supplier	Other
		√		

Additional Information: Disposal of uncleaned packages:
After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.
Disposal must be made according to official regulations. Waste code: 14 06 03 Other solvents and solvent mixtures

Is exposure adequately controlled	Yes √	No

Risk Rating Following Control Measures

High	Medium	Low √

Assessed by:	Elaine Greaves	Date:	April 2024	Review Date:	October 2025