TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: FMC001

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Mipa Silikonentferner	Pseudonym	Panel Wipe
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	Cleaning agent/ Cleaner to be applied to FLT's prior to spraying. Use: Daily, minutes at a time.	Location of process being carried out	TMHUK Paint Shop and Valeting

Identify the persons at risk	Team members [√]	Sub-contractors [ ]	Customer Team member [ ]	Public [ ]

Labelling Elements


[ ] Explosive


[√] Health Hazard


[√] Serious Health Hazard


[ ] Oxidising


[ ] Corrosive


[ ] Acute


[√] Flammable


[√] Environmental


[ ] Gas

Signal Word: DANGER

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
[ ]	[√]	[ ]	[√]	[ ]	[√]	[ ]	[ ]

Additional Information:

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
[√]	[√]	[ ]	[ ]	[ ]

Additional Information: Repeated exposure may cause skin dryness or cracking.

Control Measures

Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion when using this product. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Immediately remove all soiled and contaminated clothing
Wear PPE as listed below.
Wash hands before breaks and at the end of work. Keep away from foodstuffs, beverages and feed.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: FMC001

Is health surveilance or monitoring required?	Yes [ ]	No [√]
Provide details:		

Personal Protective Equipment Required

							
Dust Mask [ ]	Visor [ ]	Respirator [√]	Goggles [√]	Gloves [√]	Overalls [√]	Footwear [√]	Other [ ]

Additional Information: Gloves – EN374. Tightly sealed Goggles

First Aid Measures	
Inhalation:	Supply fresh air; consult doctor in case of complaints.
Skin Contact:	Immediately wash with water and soap and rinse thoroughly.
Eye Contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.
Ingestion:	Seek immediate medical advice.

Storage

Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. Keep out of reach of children.

Spillage

See SWP-19. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

Disposal of Substance & Contaminated Containers

Hazardous Waste [ ]	General Waste [ ]	Return to Depot [√]	Return to Supplier [ ]	Other [ ]

Additional Information:

Is exposure adequately controlled	Yes [√]	No [ ]

Risk Rating Following Control Measures

High [ ] Medium [ ] Low [√]

Assessed by:	Elaine Greaves	Date:	September 2026	Review Date:	March 2028