TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: FMC023-15

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Tardis	Pseudonym	Tardis – Cleaning Agent
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	Use: Applied to trucks to remove Tar & Glue residue etc. used daily, 5 or 10 minutes at a time	Location of process being carried out	TMHUK Valeting and wash down area. Designated are for charger prep.

Identify the persons at risk	Team members √	Sub-contractors ☐	Customer Team member ☐	Public ☐

Labelling Elements

 ☐ Explosive

 √ Health Hazard

 √ Serious Health Hazard

 ☐ Oxidising

 ☐ Corrosive

 ☐ Acute

 √ Flammable

 ☐ Environmental

 ☐ Gas

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	√	☐	☐	☐	√	☐	☐

Additional Information:

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
√	√	√	√	☐

Additional Information: Irritant. Aspiration hazard if swallowed.

Control Measures

This product is not recommended for any industrial, professional or consumer use other than the Identified uses described on the MSDS. For professional use only.
Read and follow manufacturer's recommendations. Wear protective clothing as described below. Keep away from food, drink and animal feeding stuffs.
Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. In use may form flammable/explosive vapour-air mixture. Vapours may accumulate on the floor and in low-lying areas. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.
Use only in small amounts, applied by rag onto the area and washed/wiped off.
Wash promptly if skin becomes contaminated. Do not eat, drink or smoke when using this product.
Wash at the end of each work shift and before eating, smoking and using the toilet. Take off contaminated

clothing before leaving workplace and wash before reuse.
This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed. To be used in small quantities Only.

Is health surveilance or monitoring required?	Yes ☐	No √

Provide details:

Personal Protective Equipment Required

 ☐	 ☐	 ☐	 √	 √	 √	 √	 √
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other

Additional Information: Chemical-resistant, impervious gloves. Eyewash station to be available

First Aid Measures

Inhalation:	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Skin Contact:	Rinse with water.
Eye Contact:	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Ingestion:	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway.

Storage

Store away from incompatible materials. Eliminate all sources of ignition. Take precautionary measures against static discharges. Earth container and transfer equipment to eliminate sparks from static electricity. Keep away from oxidising materials, heat and flames. Keep only in the original container.
Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

Spillage

See SWP-19. Wear protective clothing as described above. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion.

COSHH Risk Assessment:

Part Number: FMC023-15

Disposal of Substance & Contaminated Containers				
☐	☐	√	☐	☐
Hazardous Waste	General Waste	Return to Depot	Return to Supplier	Other
Additional Information:				

Is exposure adequately controlled	Yes √	No ☐
Risk Rating Following Control Measures		
High ☐	Medium √	Low ☐

Assessed by:	Elaine Greaves	Date:	December 2025	Review Date:	June 2027