TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: LOCTITE7471CRC

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	LOCTITE 7471	Pseudonym	LOCTITE 7471
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT Maintenance, Primer, containing solvents. Use; Infrequent, less than weekly, seconds at a time	Location of process being carried out	TMHUK Workshops & Customer Premises

Identify the persons at risk	Team members √	Sub-contractors ☐	Customer Team member ☐	Public ☐

Labelling Elements

 ☐ Explosive

 √ Health Hazard

 ☐ Serious Health Hazard

 ☐ Oxidising

 ☐ Corrosive

 ☐ Acute

 √ Flammable

 ☐ Environmental

 ☐ Gas

Signal Word: DANGER

Hazard Type

☐	√	√	☐	☐	√	☐	☐
Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other

Additional Information: Aerosol. Vapors may cause drowsiness and dizziness.

Route of Exposure & Possible Symptoms

☐	√	√	☐	☐
Inhalation	Skin	Eyes	Ingestion	Other

Additional Information: EYE: Irritation, conjunctivitis. Repeated exposure may cause skin dryness or cracking.

Control Measures

Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

Avoid breathing vapors. Use only in well-ventilated areas. Avoid skin and eye contact. Wear PPE as listed below.
Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.
Good industrial hygiene practices should be observed.

Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Do not spray on an open flame or other ignition source. eep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep out of reach of children.

This product poses no significant risk if used as intended in the amount anticipated, and

Authorisation: QSE Manager
Approval: QSE Team

manufactures instructions are followed.							
Is health surveilance or monitoring required?	Yes ☐	No √					
Provide details:							
Personal Protective Equipment Required							
 ☐ Dust Mask	 ☐ Visor	 ☐ Respirator	 √ Goggles	 √ Gloves	 √ Overalls	 √ Footwear	 ☐ Other
			EN166	Chemical-resistant protective gloves (EN 374).	EN 14605		
Additional Information:							
First Aid Measures							
Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.						
Skin Contact:	Rinse with running water and soap. Seek medical advice.						
Eye Contact:	Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.						
Ingestion:	Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting. Seek medical advice.						

Storage				
Store in a cool, well-ventilated place. Keep away from heat and direct sunlight. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep out of reach of children.				
Spillage				
See SWP-19. Avoid skin and eye contact. Ensure adequate ventilation. Do not let product enter drains. For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.				
Disposal of Substance & Contaminated Containers				
☐ Hazardous Waste	☐ General Waste	√ Depot	☐ Return to Supplier	☐ Other
Additional Information:				

Is exposure adequately controlled	Yes √	No ☐			
Risk Rating Following Control Measures					
High ☐	Medium ☐	Low √			
Assessed by:	Elaine Greaves	Date:	October 2024	Review Date:	April 2026