TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: PROETCH-PRO

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	PRO ETCH 500 ML	Pseudonym	Etch Primer
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	Maintenance of FLT. Used daily, minutes at a time.	Location of process being carried out	FMC Paintshop

Identify the persons at risk	Team members √	Sub-contractors ☐	Customer Team member ☐	Public ☐

Labelling Elements

 ☐ Explosive

 √ Health Hazard

 ☐ Serious Health Hazard

 ☐ Oxidising

 ☐ Corrosive

 ☐ Acute

 √ Flammable

 ☐ Environmental

 ☐ Gas

Signal word Danger

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	☐	☐	☐	☐	√	☐	☐

Additional Information: Grey colour

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
√	√	√	☐	☐

Additional Information: Causes serious eye irritation. May cause drowsiness or dizziness.

Control Measures

Extremely flammable aerosol. Pressurised container: May burst if heated. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.
Harmful to aquatic life with long lasting effects.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not breathe spray. Do not inhale gases / fumes / aerosols. Ensure good ventilation/exhaustion
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed. If medical advice is needed, have product container or label at hand.

Is health surveilance or monitoring required?	Yes ☐	No √

Provide details:

COSHH Risk Assessment:

Part Number: PROETCH-PRO

Personal Protective Equipment Required							
			 √	 √	 √	 √	
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other

Additional Information: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

First Aid Measures	
Inhalation:	Supply fresh air; consult doctor in case of complaints.
Skin Contact:	Generally the product does not irritate the skin.
Eye Contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Ingestion:	Drink plenty of water and provide fresh air. Call for a doctor immediately.

Storage

Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep container tightly sealed.

Spillage

See SWP-19. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. Ensure adequate ventilation. Wear protective equipment. Keep unprotected persons away.

Disposal of Substance & Contaminated Containers

Hazardous Waste	General Waste	Depot	Return to Supplier	Other
√				

Additional Information: Dispose of contents / container in accordance with regional regulations. Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Is exposure adequately controlled	Yes √	No

Risk Rating Following Control Measures

High	Medium	Low
		√

Assessed by:	Elaine Greaves	Date:	Feb 2026	Review Date:	August 2027