TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: SDS10109PRO

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Mirror Image Product number 140-23	Pseudonym	Mirror Image Polish
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	Polishing plastic hoods and other plastic panels on exhibition trucks. max 30 minutes a day– biannually	Location of process being carried out	Workshop Painters and Valets

Identify the persons at risk	Team members [√]	Sub-contractors [ ]	Customer Team member [ ]	Public [ ]

Labelling Elements


[ ] Explosive


[√] Health Hazard


[ ] Serious Health Hazard


[ ] Oxidising


[ ] Corrosive


[ ] Acute


[ ] Flammable


[ ] Environmental


[ ] Gas

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
[ ]	[√]	[ ]	[ ]	[ ]	[√]	[ ]	[ ]

Additional Information:

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
[√]	[√]	[√]	[√]	[ ]

Additional Information: Repeated exposure may cause skin dryness or cracking.

Control Measures

Avoid spilling. Avoid contact with skin and eyes. Avoid inhalation of vapours. During application and drying, solvent vapours will be emitted.
This product must not be handled in a confined space without adequate ventilation.
Eyewash to be readily available.
Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes [ ]	No [√]

Provide details:

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: SDS10109PRO

Personal Protective Equipment Required							
							
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
				√			

Additional Information: Wear protective gloves made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves.
Frequent changes are recommended.

First Aid Measures	
Inhalation:	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Skin Contact:	Rince with water
Eye Contact:	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Ingestion:	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention immediately. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

Storage
Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store in closed original container at temperatures between 5°C and 30°C. Keep above the chemical's freezing point to avoid rupturing the container.
Spillage
See SWP-19 Avoid the spillage or runoff entering drains, sewers or watercourses. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Take care as floors and other surfaces may become slippery.
Disposal of Substance & Contaminated Containers

		√		
Hazardous Waste	General Waste	Return to Depot	Return to Supplier	Other

Additional Information:

Is exposure adequately controlled	Yes √	No	
Risk Rating Following Control Measures			
High	Medium	Low √	

Assessed by:	Elaine Greaves	Date:	September 2026	Review Date:	March 2028