TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: SDS10459PRO

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Jelsol	Pseudonym	Graffiti Remover
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	Use: Applied to trucks to removed labels etc. used daily, 5 or 10 minutes at a time	Location of process being carried out	TMHUK Workshops and prep areas

Identify the persons at risk	Team members	Sub-contractors	Customer Team member	Public
	√			

Labelling Elements


Explosive ☐


Health Hazard √


Serious Health Hazard ☑


Oxidising ☐


Corrosive ☐


Acute ☐


Flammable √


Environmental ☐


Gas ☐

Signal Word: DANGER

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
√		√	√		√		

Additional Information:

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
√	√	√		

Additional Information: Irritant to skin and eyes. Inhalation: Headache. Exhaustion and weakness.

Control Measures

Read and follow manufacturer's recommendations.
Do not handle until all safety precautions have been read and understood.
Extremely flammable aerosol. Pressurised container: may burst if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breatje vapours, spray.
Do not reuse empty containers. Protect from sunlight> Do not expose to temperatures exceeding 50C.
Wear protective clothing as described below and in SWP-32. Eyewash station and safety shower to be readily available.
Use only outdoors or where there is adequate ventilation.

Keep away from food, drink and animal feeding stuffs.
Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Clean equipment and the work area every day.

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: SDS10459PRO

Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes [ ]	No [√]

Provide details:

Personal Protective Equipment Required



Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other
[ ]	[ ]	[ ]	[√]	[√]	[√]	[√]	[ ]

Additional Information: Tight-fitting safety goggles. Gloves should comply with European Standard EN374. Check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

First Aid Measures

Inhalation:	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Skin Contact:	It is important to remove the substance from the skin immediately. Take off immediately all contaminated clothing. Remove contamination with soap and water or recognised skin cleansing agent. Get medical attention.
Eye Contact:	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes. If eye irritation persists, get medical advice/attention.
Ingestion:	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Store away from incompatible materials (see Data Sheet). Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Do not store near heat sources or expose to high temperatures. Bund storage facilities to prevent soil and water pollution in the event of spillage.

Spillage

See SWP-19 Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.

Disposal of Substance & Contaminated Containers

COSHH Risk Assessment:

Part Number: SDS10459PRO

[√]	[ ]	[√]	[ ]	[ ]
Hazardous Waste	General Waste	Return to Depot	Return to Supplier	Other

Additional Information:

Is exposure adequately controlled	Yes [√]	No [ ]			
Risk Rating Following Control Measures					
High [ ]	Medium [ ]	Low [√]			
Assessed by:	Martin Ratcliffe	Date:	September 2026	Review Date:	March 2028