TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: SDS11192PRO

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	Fallout Remover	Pseudonym	Fallout Remover
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	FLT refurbishment/ maintenance. USE: daily, minutes at a time Cleaning Agent	Location of process being carried out	Toyota Workshops

Identify the persons at risk	Team members	Sub-contractors	Customer Team member	Public
	√			

Labelling Elements


Explosive ☐


Health Hazard ☐


Serious Health Hazard ☐


Oxidising ☐


Corrosive ☑


Acute ☐


Flammable ☐


Environmental ☐


Gas ☐

Signal Word: Danger

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	☐	☐	☐	☐	√	☐	☐

Additional Information: Clear

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
☐	√	√	√	☐

Additional Information: Causes serious eye damage, Irritant.

Control Measures

Keep out of reach of children. Wash contaminated skin thoroughly after handling.
Avoid spilling. Avoid contact with skin and eyes.
Wear protective clothing as described below. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills.
Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Keep container tightly sealed when not in use. Avoid release to the environment

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Is health surveilance or monitoring required?	Yes	No
	☐	√

Provide details:

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: SDS11192PRO

Personal Protective Equipment Required							
			√	√	√	√	
Dust Mask	Visor	Respirator	Goggles	Gloves	Overalls	Footwear	Other

Additional Information: Provide adequate ventilation. Ensure Eyewash station is available.

First Aid Measures	
Inhalation:	Get medical attention if any discomfort continues.
Skin Contact:	Remove contaminated clothing. Rinse with water. Use suitable lotion to moisturise skin. Get medical attention if any discomfort continues.
Eye Contact:	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.
Ingestion:	Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues

Storage

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store in closed original container at temperatures between 5°C and 30°C. Keep above the chemical's freezing point to avoid rupturing the container.
Storage class: Chemical storage.

Spillage

See SWP-19. Stop leak if possible without risk. Large Spillages: Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Take care as floors and other surfaces may become slippery. Avoid the spillage or runoff entering drains, sewers or watercourses. Flush away spillage with plenty of water. Wash thoroughly after dealing with a spillage. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

Disposal of Substance & Contaminated Containers

	√			
Hazardous Waste	General Waste	Depot	Return to Supplier	Other

Additional Information: The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. Do not empty into drains.

Is exposure adequately controlled	Yes √	No

Risk Rating Following Control Measures		
High	Medium	Low √

Assessed by:	Elaine Greaves	Date:	December 2025	Review Date:	June 2027