TOYOTA

MATERIAL HANDLING

COSHH Risk Assessment:

Part Number: SDS21535PRO

Name of Substance involved in the process *(a copy of the current safety data sheet is available)*	EVO 3 Product number 443-1	Pseudonym	EVO 3 Polish
Describe the activity or work process & exposure *(Inc. how long/how often this is carried out)*	Polishing plastic hoods and other plastic panels on exhibition trucks. max 30 minutes a day– biannually	Location of process being carried out	Workshop Painters and Valetors

Identify the persons at risk	Team members	Sub-contractors	Customer Team member	Public
	√			

Labelling Elements

 ☐ Explosive

 ☐ Health Hazard

 ☐ Serious Health Hazard

 ☐ Oxidising

 ☐ Corrosive

 ☐ Acute

 ☐ Flammable

 ☐ Environmental

 ☐ Gas

Not Classified

Hazard Type

Gas	Vapour	Mist	Fume	Dust	Liquid	Solid	Other
☐	☐	√	☐	☐	√	☐	☐

Additional Information:

Route of Exposure & Possible Symptoms

Inhalation	Skin	Eyes	Ingestion	Other
☐	√	√	☐	☐

Additional Information: Irritant

Control Measures

Read and follow manufacturer's recommendations.

Wear protective clothing as described below.
Keep away from food, drink and animal feeding stuffs.
Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists.
Wash promptly if skin becomes contaminated. Take off contaminated clothing.
Wash contaminated clothing before reuse.
Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

Good general ventilation should be adequate to control worker exposure to airborne contaminants.

This product poses no significant risk if used as intended in the amount anticipated, and manufactures instructions are followed.

Authorisation: QSE Manager
Approval: QSE Team

COSHH Risk Assessment:

Part Number: SDS21535PRO

Is health surveilance or monitoring required?	Yes ☐	No √

Provide details:

Personal Protective Equipment Required


Dust Mask ☐


Visor ☐


Respirator ☐


Goggles ☐


Gloves √


Overalls ☐


Footwear ☐


Other ☐

Additional Information: Eye protection must be worn if using in high quantities and a risk assessment indicates eye contact is possible. Wear Chemical-resistant, impervious gloves (EN374)

First Aid Measures

Inhalation:	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Skin Contact:	Remove affected person from source of contamination. Rinse immediately with plenty of water.
Eye Contact:	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Ingestion:	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

Storage

Keep stock levels to a minimum. Store away from incompatible materials (see Section msds). Store in accordance with local regulations.

Spillage

See SWP-19. Clear up spills immediately and dispose of waste safely. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations.

Disposal of Substance & Contaminated Containers

Hazardous Waste ☐ General Waste ☐ Return to Depot √ Return to Supplier ☐ Other ☐

Additional Information:

Is exposure adequately controlled	Yes √	No ☐

Risk Rating Following Control Measures

High ☐ Medium ☐ Low √

Assessed by:	Elaine Greaves	Date:	November 2024	Review Date:	May 2026